

OVERVIEW

The GX2 Gateway enables any LC&D panel-based or wireless system to be monitored and controlled using GX2 lighting control software. Once connected to a system, the GX2 Gateway provides many advanced features like energy analytics, grouping, alerts and time schedule management. The GX2 lighting control software is accessible on various devices – from LED/LCD TVs (for publicly displaying energy usage and savings) to any modern web browser running on PCs, laptops, or mobile devices on a local network. Its small size allows it to easily fit into any space in a server room or even behind a screen.

FEATURES

- Factory pre-configured GX2 lighting control software
- Multiple user access to GX2 lighting control software
- HDMI port for connecting to a variety of LED and Plasma screens
- A compact size to easily fit into any server room

SPECIFICATIONS

Enclosure dimensions:	7.5" w x 7.5" d x 1.4" h
Weight:	1.8 lbs
Memory:	4GB DDR3 1333MHz SO DIMM
Storage:	1GB SSD (Solid State Drive)
Graphics:	Intel Integrated Graphics
Networking:	On-Board Gigabit/100/1000T Ethernet
Power supply inputs:	12VDC (5A 60W power adapter)
Operating temperature:	32–131° F (0–55° C)
Shock:	3,920 m/s ² (400G) 2ms (operating) 8,820 m/s ² (900G) 1ms (non-operating)

Warranty

Three-year limited warranty. Complete warranty terms located at:
www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx

Note: Actual performance may differ as a result of end-user environment and application.

Specifications subject to change without notice.

AcuityControls™

LC&D™

GX2 Gateway




ORDERING INFORMATION

GX2 GATEWAY

System

GX2 GATEWAY



Title 24 System Component