

## FEATURES & SPECIFICATIONS

### INTENDED USE

Provides maintenance-free, energy-efficient accent and/or task lighting in residential and light commercial applications. Mix and match fitter with any number of decorative shades/diffusers from Lithonia Lighting to create a look that perfectly compliments any décor. Ideal for mounting over kitchen islands, countertops, bars, desks and tables.

### CONSTRUCTION

Cast aluminum fitter and matching canopy is finished in a bronze finish.

Includes three set screws which hold decorative shades that mount to the inside of the fitter. These shades have a standard 2-1/4" neck.

Decorative shades that mount to the outside of the fitter include decorative finials or decorative rods, three bronze and three polished brushed nickel, that screw into the fitter.

Decorative shades are available in hand-blown glass, prismatic glass or metal. All decorative shades fit both fitter styles.

Decorative shades sold separately.

### OPTICS

Each fitter contains three 3000K high-performance LEDs which maintain 274 lumen output at 50,000-hour life.

### ELECTRICAL

LED driver is 120V and operates at 60Hz.

Fully dimmable down to 10%. Works with most standard incandescent dimmers. See chart on second page for suggested dimmers.

### INSTALLATION

Suspended mount from ceiling. Includes 78" of cable for tool-free mounting height adjustment. Excess cable fits within canopy - no cutting necessary.

All mounting hardware included.

### LISTINGS

UL listed to U.S. and Canadian safety standards.

### WARRANTY

5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at: [www.acuitybrands.com/support/warranty/terms-and-conditions](http://www.acuitybrands.com/support/warranty/terms-and-conditions)

**NOTE:** Actual performance may differ as a result of end-user environment and application.

All values are design or typical values, measured under laboratory conditions at 25 °C.

Specifications subject to change without notice.

Catalog Number
Notes
Type

## LED Mini-Pendant Fitter with Mix-and-Match Shades

# MDP

HIGH-PERFORMANCE LED



Bullet Fitter



See page 2 for additional shade images

### Dimensions

#### Bullet Fitter:

Canopy Width: 5" (12.7)

Canopy Height: 1-7/8" (4.8)

Fitter Width: 2-3/4" (7)

Fitter Height: 2" (5.1)

Bullet fitter includes 78" of cable for tool-free mounting height adjustment.

All dimensions are inches (centimeters).

## ORDERING INFORMATION

For shortest lead times, configure products using **bolded options**.

**Example:** MDPB BZ

Series <sup>1</sup>	Finish
<b>MDPB</b> Bullet LED mini-pendant fitter	<b>BZ</b> Bronze

### Notes

1 Glass shades must be ordered separately. See Shade Ordering Information.

## SHADE ORDERING INFORMATION

For shortest lead times, configure products using **bolded options**.

**Example:** DBEL 1001


Model (see page 2 for shade images)			
<b>DBEL 1001</b> Bell shade in opal white finish	<b>DMCN BZ</b> Metal cone shade in bronze finish	<b>DG WV 1003</b> Cylinder wave shade in frosted white finish	
<b>DCNE 1001</b> Cone shade in opal white finish	<b>DMCN BNP</b> Metal cone shade in polished brushed nickel finish	<b>DSCL 1010</b> Short cylinder shade in white drizzle finish	

# LED Mini-Pendant Fitters and Shades

## PHOTOMETRICS

Actual wattage may differ by +/- 5% when operating at 120V +/- 10%.  
Actual performance may differ as a result of end-user environment and application.

Lithonia Lighting




A Program of the U.S. DOE

<b>Light Output (Lumens)</b>	<b>274</b>
<b>Watts</b>	<b>9.5</b>
<b>Lumens per Watt (Efficacy)</b>	<b>28</b>

<b>Color Accuracy</b>	<b>86</b>
Color Rendering Index (CRI)	

**Light Color**  
Correlated Color Temperature (CCT) **2851 (Warm White)**



2700K   3000K   4500K   6500K

All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit [www.lightingfacts.com](http://www.lightingfacts.com) for the Label Reference Guide.

Registration Number: NJSM-ZRKT4D  
Model Number: MDP  
Type: Surface-mounted fixture (other)

Suggested Dimmers		
<i>The MDP Series is designed to operate with most standard Triac Based (Forward Phase-Control or Leading Edge) dimmers and is not compatible with 0-10v dimming systems. The following is a list of dimmers tested with the MDP Series and does not imply any guarantee or warranty of compatibility with a particular application. Unlisted dimmers do not imply non-compatibility.</i>		
Manufacturer	Series	Part Number(s)
Leviton	Illumitech	IPI06-XXX
Leviton	Trimatron	6602-1, 6681-X, 6683-X, 6684-X, 700-X, 705-X
Leviton	SureSlide	6631
Leviton	True Touch	6606-1LM
Lutron	Skylark	S-600, S2-LH
Lutron	Nova T	NTELV-600
Lutron	Faedra	FAELV-500-XX
Lutron	Acenti	ACE06-XXX
Lutron	Vizia	VZE04

Note: When the installation exceeds 10 fixtures on a single dimmer or distribution lengths exceed 100 feet, please confirm that the end product performs properly. This is caused by a high degree of variability in the triac dimmers.

## SHADES

Shades/diffusers must be ordered separately from fitters.

All decorative shades are hand-blown glass (variations in pattern may exist) unless otherwise specified. Shades using decorative rods/finials include rods/finials in both bronze and polished brushed nickel.



**DGWV 1003**  
Frosted White  
Cylinder Wave  
4" W X 7-3/4" H



**DBEL 1001**  
Opal White Bell  
4-1/2" W X 6" H



**DSCL 1010**  
White Drizzle  
Short Cylinder  
3-3/8" W X 6" H



**DCNE 1001**  
Opal White Cone  
5-5/8" W X 3" H



**DMCN BZ**  
Bronze Cone  
(Metal)  
5-3/8" W X 3" H



**DMCN BNP**  
Polished Brushed  
Nickel Cone (Metal)  
5-3/8" W X 3" H