

SLOT

Family Cross Reference

PERFORMANCE

| | | SLOT 1 | | SLOT 2 | | SLOT 4 | |
|--------------------------------------|----------------------|--------------|------------------|--------------|--------------|--------------|--------------|
| | | Pendant/Wall | Surface/Recessed | Pendant/Wall | Surface | Pendant/Wall | Surface |
| Source | | I/D/ID | D | I/D/ID | D | I/D/ID | D |
| Nominal Lumen Output | Direct | 200-1000 LMF | 200-1000 LMF | 300-1500 LMF | 300-1500 LMF | 300-1500 LMF | 300-1500 LMF |
| | Indirect | 400-1200 LMF | | 300-1500 LMF | | 300-1500 LMF | |
| Lumens/Watt | Direct | 109-119 LPW | 109-119 LPW | 105-117 LPW | 105-117 LPW | 111-126 LPW | 111-126 LPW |
| | Indirect | 151-173 LPW | | 155-162 LPW | | 159-166 LPW | |
| Modulus™ Networked Power & Control | | M | M | | | | |
| Integral Driver | | I | I | I | I | I | I |
| Dynamic Tunable White 2700K to 6500K | | M | M | • | • | • | • |
| Low UGR | | • | • | • | • | • | • |
| Participates in Declare | | | | • | • | • | • |
| Run length (min. increment) | | feet/inches | feet/inches | inches | inches | inches | inches |
| Embedded Control Options | 0-10v | • | • | • | • | • | • |
| | nLight® | M | M | • | • | • | • |
| | nLight® Air | M | M | • | • | • | • |
| | Occ/Daylight Sensors | M | M | • | • | • | • |
| | Emergency | M | M | • | • | • | • |
| Dim to 1% | | • | • | • | • | • | • |
| Dim to 0.1% | | M | M | • | • | • | • |
| DLC Listed | | | | • | • | • | • |
| DLC Premium | | | | • | | • | |

- = Available with both Integral Driver & Modulus power and control options
- M = Available with Modulus power and control option
- I = Available with Integral Driver power and control option

SLOT

Family Cross Reference

FEATURES & OPTICS

| | | SLOT 1 | | SLOT 2 | | SLOT 4 | |
|---|-----------------------|--------------|------------------|--------------|---------|--------------|---------|
| | | Pendant/Wall | Surface/Recessed | Pendant/Wall | Surface | Pendant/Wall | Surface |
| Illuminated "L" Connectors: 40°-160° | | • | • | • | • | • | • |
| Illuminated "T" and "X" Connectors: 90° | | P | • | P | • | P | • |
| Direct Optics | Asymmetric | • | • | | | | |
| | Batwing | • | • | P | • | • | • |
| | Lambertian | • | • | • | • | • | • |
| | Wall Graze | • | • | • | • | • | • |
| | Wallwash | • | • | P | • | P | • |
| Direct Shielding | Baffles | • | • | • | • | • | • |
| | Continuous Flush Lens | | | • | • | • | • |
| | Drop Lenses* | • | • | • | • | • | • |
| | Edge View Lens | • | • | • | • | • | • |
| | Flush Lens | • | • | • | • | • | • |
| | Regressed Lens | | R | | | | |
| Indirect Optics | Asymmetric | • | | • | | • | |
| | Batwing | P | | P | | P | |
| | Lambertian | • | | • | | • | |
| Indirect Shielding | Top Glow | • | | • | | • | |

* = Can also be used as indirect shielding
 • = All
 P = Pendant Only
 R = Recessed Only