

## Emergency Lighting for All Languages

The EXRM, ECRM, and ECBRM by Lithonia Lighting® are highperforming signs and combos with directional "Running Man" face plates. These fixtures safely identify all exits and provide a minimum of 90-minutes of illumination upon the loss of AC power. All three products are ideal for public environments like airports, schools and restaurants. Don't let translation be a barrier to safely exiting any building.

## **Features and Benefits:**

- Single or double-sided signs
- Ceiling, wall or flush mount
- Standard and Arrow panels included
- Automatically performs monthly and annual testing with multi-status diagnostics functions
- Quick installation







Learn more about the EXRM, ECRM, and ECBRM at www.lithonia.com

## Commercial LED Running Man Signs and Combos

	EXRM	ECRM	ECBRM
			€ R
Best Use	Means of egress marking	Means of egress markings and illumination over doorways	Means of egress markings and illumination over doorways
Mounting	Top, side, and back mount	Top, side, and back mount	Top, side, and back mount
Housing/Construction	White thermoplastic. 5VA flame rated and impact-resistant	White thermoplastic, classic square, dual lamp heads. 5VA flame rated and impact-resistant	White thermoplastic, adjustable lightbar. 5VA flame rated and impact-resistant
Ambient Temperature Range	0°C - 50°C (32°F - 122°F)	0°C - 50°C (32°F - 122°F)	0°C - 50°C (32°F - 122°F)
Voltage	Dual-voltage 120/347 standard	Dual-voltage 120/347 standard	Dual-voltage 120/347 standard
Optics	-	1W / white LED lamp head	up to 3W
Weight	2 lbs	3.75 lbs	3.75 lbs
Certification/Ratings i.e., DLC, CSA, etc.	CSA Damp, CSA 22.2 No. 141, NFPA 101, FCC, OSHA	CSA Damp, CSA 22.2 No. 141, NFPA 101, FCC, OSHA	CSA Damp, CSA 22.2 No. 141, NFPA 101, FCC, OSHA
Battery	9.6V maintenance-free, rechargeable, nickel-cadmium	9.6V maintenance-free, rechargeable, nickel-cadmium	9.6V maintenance-free, rechargeable, nickel-cadmium
Test Switch	Yes	Yes	Yes
Emergency Backup	90 minutes	90 minutes	90 minutes
Remote Capacity	Yes, with EL option using ERE remotes	Yes, with HO option using ERE remotes	Yes, using ERE remotes
Acuity Controls	No	No	No
Warranty	5-year limited warranty	5-year limited warranty	5-year limited warranty
Application	Small commercial indoor applications requiring lower mounting heights	Small commercial indoor applications requiring lower mounting heights	Small commercial indoor applications requiring lower mounting heights









