

FEATURES & SPECIFICATIONS

INTENDED USE — Ideal one-for-one replacement of conventional lighting systems such as HID and fluorescent. For use in light Industrial applications such as, warehousing and other large indoor spaces with mounting heights ranging from 10' – permitted. **Certain airborne contaminants can diminish integrity of acrylic and LED's.** [Click here for Acrylic Environmental Compatibility table for suitable uses.](#)

Certain airborne contaminants, including condensation, may adversely affect the functioning of LEDs and other electronic components, depending on various factors such as concentrations of the contaminants, ventilation, and temperature at the end-user location. [Click here for a list of substances that may not be suitable for interaction with LEDs and other electronic components.](#)

CONSTRUCTION — Extruded aluminum channels enable superior thermal performance. Glare Control acrylic lens diffuses light source and reduces glare while protecting LEDs. Lens meets DLC 5.1 standards for UGR (Unified Glare Rating).

ELECTRICAL — 70% lumen maintenance at > 100,000 hours. Thermally protected driver standard with 0-10V dimming. Luminaire surge protection level: designed to withstand up to 6kV/3kA per ANSI C82.77-5-2015 Multi-volt driver, 120-277V standard.

INSTALLATION — Fixture is suitable for mounting by chain, cable, surface-mount bracket, pendant monopoint, or hook monopoint. Utilizing appropriate mounting accessory. Designed for use in ambient temperatures ranging from -40°C to 55°C when suspended 18" off ceiling. Surface mount to 45°C ambient operation.

Note: Temperature cycling, or variations can potentially produce condensation; please consult factory.

LISTINGS — CSA listed. Damp location listed.

DesignLights Consortium® (DLC) Premium qualified product. Not all versions of this product may be DLC Premium qualified. Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which versions are qualified.

GOVERNMENT PROCUREMENT —

BAA – Buy American Act: This product is available in a version that qualifies as a domestic end product under the Buy American Act as implemented in the FAR and DFARS.

BABA – Build America Buy America: This product is available in a version that qualifies as produced in the United States under the definitions of the Build America, Buy America Act, as implemented by 2 C.F.R. Part 184 and other agency implementing regulations, including Department of Transportation regulations. Please refer to www.acuitybrands.com/resources/buy-american for additional information.

WARRANTY — 5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at: www.acuitybrands.com/support/warranty/terms-and-conditions

Note: Actual performance may differ as a result of end-user environment and application.

All values are design or typical values, measured under laboratory conditions at 25 °C.

The product images shown are for illustration purposes only and may not be an exact representation of the product.

Specifications subject to change without notice.

Catalog Number
Notes
Type

LED High Bay

COMPACT PRO™

9,000 through 60,000 Lumens




Standard Part Number	Stock Part Number	Stock Part Number CI Code	DLC Product ID	DLC Premium?
CPHB 12000LM SEF GCL MD MVOLT GZ10 40K 80CRI DWH	CPHB 12LM MVOLT 40K	*268SAH	PAMXQBT8	Yes
CPHB 12000LM SEF GCL MD MVOLT GZ10 50K 80CRI DWH	CPHB 12LM MVOLT 50K	*2681J0	POQ23DMQ	Yes
CPHB 15000LM SEF GCL MD MVOLT GZ10 40K 80CRI DWH	CPHB 15LM MVOLT 40K	*2681J2	PLPPHUG	Yes
CPHB 15000LM SEF GCL MD MVOLT GZ10 50K 80CRI DWH	CPHB 15LM MVOLT 50K	*2681J5	PJ97Z0F9	Yes
CPHB 18000LM SEF GCL MD MVOLT GZ10 40K 80CRI DWH	CPHB 18LM MVOLT 40K	*268SAJ	PWHG1E01	Yes
CPHB 18000LM SEF GCL MD MVOLT GZ10 50K 80CRI DWH	CPHB 18LM MVOLT 50K	*2681J9	PSRNYSS1	Yes
CPHB 24000LM SEF GCL MD MVOLT GZ10 40K 80CRI DWH	CPHB 24LM MVOLT 40K	*2681JE	PC2IBASD	Yes
CPHB 24000LM SEF GCL MD MVOLT GZ10 50K 80CRI DWH	CPHB 24LM MVOLT 50K	*2681JL	P7DUT8S1	Yes
CPHB 30000LM SEF GCL MD MVOLT GZ10 40K 80CRI DWH	CPHB 30LM MVOLT 40K	*2681JM	PRXQVN2Q	Yes
CPHB 30000LM SEF GCL MD MVOLT GZ10 50K 80CRI DWH	CPHB 30LM MVOLT 50K	*2681JP	PDAUA08P	Yes



design select

Items marked by a shaded background qualify for the Design Select program and ship in 15 days or less. To learn more about Design Select, visit www.acuitybrands.com/designselect. *See ordering tree for details




ORDERING INFORMATION

Lead times will vary depending on options selected. Consult with your sales representative.

Example: CPHB 24000LM SEF GCL MD 120 GZ10 40K 80CRI CPSBW SSE PIRHKO HL DWH

CPHB				GCL				GZ10			
Series	Lumens	Performance Package	Lens	Distribution	Voltage	Driver	Color Temperature	Color Rendering Index			
CPHB Compact Pro High Bay	9000LM	9,000 lumens	SEF Standard Efficiency	GCL Glare Control Lens	MD Medium Distribution	MVOLT 120-277V	GZ10 0-10V dimming driver	35K 3500 K	70CRI 70 CRI		
	12000LM	12,000 lumens				120 120V					
	15000LM	15,000 lumens	HEF High Efficiency	ND Narrow Distribution	208 208V	40K 4000 K	80CRI 80 CRI				
	18000LM	18,000 lumens ‡			240 240V						
	24000LM	24,000 lumens	WD Wide Distribution	277 277V	50K 5000 K	90CRI 90 CRI					
	30000LM	30,000 lumens		347 347V ‡							
	36000LM	36,000 lumens		480 480V ‡							
	48000LM	48,000 lumens		HVOLT 347-480V ‡							
60000LM	60,000 lumens										

Options		DWH
		Finish
BAA	Buy America(n) Act and/or Build America Buy America Qualified	DWH Gloss White
Emergency Options: ‡		
E10W	IOTA 10W emergency battery pack, Constant Power, Certified in CA Title 20 MAEDBS, Self-diagnostics (LINK) ‡	
E10WCP	10W emergency battery pack, Certified in CA Title 20 MAEDBS ‡	
E15WMCP	15W emergency battery pack, Certified in CA Title 20 MAEDBS ‡	
IE10WMCP	10W emergency battery pack, Certified in CA Title 20 MAEDBS ‡	
IE15WMCP	15W emergency battery pack, Certified in CA Title 20 MAEDBS ‡	
IE20WCPHE	Iota 20W emergency battery pack, Certified in CA Title 20 MAEDBS ‡	
ETS	Generator Transfer Device ‡	
WGX	Wireguard installed	
IMP	Integrated modular plug ‡	
SPD	Additional 10kV surge protection device ‡	
RRL_	RELOC -Ready luminaire. (Not available with Haleon sensor options). See page 14 for ordering information	
OCS	RELOC OnePass selectable cable 6' installed ‡ ‡	
OCS4C	RELOC One Pass™ selectable cable 6' installed. ‡ ‡	
2470P	24/7 operation, factory installed battery with 3-conductor cordset and Reloc, with on/off controlled by sensor rather than switch, the normal hot and unswitched hot wired together in the fixture. Consult local codes to determine if this is allowable	
JP	Job Pack ‡	
Cord Sets: ‡		
CPSBW	6' white damp location cord with straight blade plug (voltage will match fixture, 120, 208, 240, or 277V only)	
CPTLW	6' white damp location cord with 15 amp twist-lock plug (voltage will match fixture) ‡	
CPTL20AW	6' white damp location cord with 20 amp twist lock plug (voltage will match fixture) ‡	
CNPW	6' white cord, no plug	
CNP4CW	6' white cord, 4 conductors (for use with battery)	
CNP5CDW	6' white cord, 5 conductors (includes dimming leads)	
Individual Controls: ‡ ‡		
SSE PIRHKO	360° integral high mount motion sensor with standard on/off operation	
SSE PIRHKO HL	360° integral high mount motion sensor with high/low/(off) occupancy operation. For High/Low/(never off)	
SSE PIRHKO P	360° integral high mount motion sensor with on/off switching photocell	
SSE APIRHKO	360° integral high mount motion sensor with dimming & switching photocell	
SSE APIRHKO ANL	360° integral high mount motion sensor with High/Low occupancy dimming & auto-dimming photocell	
*For 360° integral LOW MOUNT sensors, remove "H". For High Mount AISLEWAY sensors, replace "H" in nomenclature with "A".		
nLight AIR Wireless Controls:		
NLTAIR2	Embedded wireless controls by nLight	
NLTAIR2 KO	Embedded wireless controls by nLight, Control mounted external to the luminaire via a KO ‡	
NLTAIREM2 KO	Embedded wireless controls by nLight with UL924 listed emergency operation Control mounted external to the luminaire via a KO ‡	
NLTAIRER2 KO	Embedded wireless controls by nLight with UL924 listed emergency operation via power sense leads, mounted external to fixture via KO ‡	
NLTAIR2 APIRH*	Embedded wireless controls by nLight, Passive Infrared Occ sensor with auto-dimming photocell for high mounting height applications	
NLTAIREM2 APIRH*	Embedded wireless controls by nLight, with UL924 listed emergency operation, Passive Infrared Occ sensor with auto-dimming photocell for high mounting height applications	
*For 360° integral LOW MOUNT sensors, remove "H" from the nomenclature. For AISLE MOUNT sensors, remove "H" replace with "A".		
NLTAIR2 APIRHKO*	Embedded wireless controls by nLight, Knock out mounted Passive Infrared Occ sensor with auto-dimming photocell for high mounting height applications	
NLTAIR2 APIRAKO	Embedded wireless controls by nLight, Knock out mounted Passive Infrared Occ sensor with auto-dimming photocell for Aisleway applications	
NLTAIRER2 APIRKO	Embedded wireless controls by nLight with UL924 listed emergency operation via power sense leads, Control mounted external to the luminaire via a KO ‡	
NLTAIREM2 APIRHKO*	Embedded wireless controls by nLight with UL924 listed emergency operation, Knock out mounted Passive Infrared Occ sensor with auto-dimming photocell for high mounting height applications	
NLTAIREM2 APIRAKO	Embedded wireless controls by nLight with UL924 listed emergency operation, Knock out mounted Passive Infrared Occ sensor with auto-dimming photocell for Aisleway applications	

Accessories: Order as separate catalog number.		
Mounting:		
IBAC120 M100	Aircraft cable 10' with hook (one pair)	
IBAC240 M75	Aircraft cable 20' with hook (one pair)	
IBHMP	Hook monopoint	
CPHBPMP5M	Pendant Monopoint splice box with 3/4" hub (for 9000LM – 18000LM) ‡	
CPHBPMPMD	Pendant Monopoint splice box with 3/4" hub (for 24000LM – 30000LM) ‡	
CPHBPMP1G	Pendant Monopoint splice box with 3/4" hub (for 36000LM – 60000LM) ‡	
ZACVH	Aircraft 10' V hanger (one pair)	
HC36	Hanger chain, 36" (one pair)	
THUNJ2	Tong hanger surface mount bracket ‡	
Wire guards:		
WGCPHBSM	Wire guard for CPHB (9000LM – 18000LM)	
WGCPHBMD	Wire guard for CPHB (24000LM – 30000LM)	
WGCPHBLG	Wire guard for CPHB (36000LM – 60000LM)	
		
Cord sets for IMP option: ‡		
CS1WIMP	Straight plug, 120V	
CS3WIMP	Twist-lock, 120V	
CS7WIMP	Straight plug, 277V	
CS11WIMP	Twist-lock, 277V	
CS93WIMP	600V 50 white cord, no plug (no voltage required)	

‡ Option Value Ordering Restrictions	
Option Value	Ordering Restrictions
18000LM	Not available with HVOLT. Not available with ETS or ER sensor option. When 18000LM requires 347 or 480 volt; the fixture utilizes a step-down transformer.
2470P	Requires cord or reloc, battery and sensor options. Not available with 4 conductor cord sets. CPHB will be wired from the factory for 24/7 operation (via cord or Reloc), with on/off controlled by sensor rather than switch. Consult local codes to determine if this is allowable.
347	Fixture includes an additional 10kV surge protector. When ordered with 18000LM, includes step down transformer.
480	Fixture includes an additional 10kV surge protector. When ordered with 18000LM, includes step down transformer.
Cord Sets	Must specify voltage on cord sets with plugs.
Cord Sets for IMP	Fixture must be ordered with IMP option. All cord sets are 18/3, 6' white.
CPHBPMP5M/MD/LG	Pendant monopoint splice boxes will require wiring from access plate to splice box KO if power is being dropped through pendant conduit. Fixture does not have a KO in center to pull power out of driver channel through splice box. Not for use with battery pack.
CPTL20AW	Required on 347 and 480 volt.
Emergency Options	May alter fixture construction. Consult line art for dimensions. Batteries not for use with pendant mount option. If cord set is needed, use CNP4CW which will have normal hot and unswitched hot exiting cord set. Not available with IMP, ETS, or THUN options.
E10W	Available with MVOLT, 120, 208, 240, or 277. (120, 208, 240, or 277 when any other option ordered such as cord and plug requires voltage to be specified). Available with lumen packages 24000LM – 60000LM.
E10WCP	Available with MVOLT, 120, 208, 240, or 277. (120, 208, 240, or 277 when any other option ordered such as cord and plug requires voltage to be specified). Max ambient operating temperature of 35°C. Includes an additional 10kV surge protector on the unswitched, battery hot. Only available with 9000LM – 18000LM.
E15WMC	Available with MVOLT, 120, 208, 240, or 277. (120, 208, 240, or 277 when any other option ordered such as cord and plug requires voltage to be specified). Factory installation only. Not approved for field installation. Max ambient operating temperature of 35°C. Includes an additional 10kV surge protector on the unswitched, battery hot.
ETS	MVOLT only. Not available with 18000LM. Not available with cord sets or batteries. When sensor is required, use "ER" sensor option. Utilizes ETS 924 DR component. Includes an additional 10kV surge protector.
HVOLT	Fixture includes an additional 10kV surge protector. Not valid with 18000LM.
IE10WMC	Available with HVOLT, 347 or 480. (347 and 480 when any other option ordered such as cord with plug requires voltage to be specified). Not available with 18000LM.
IE15WMC	Available with HVOLT, 347 or 480. (347 and 480 when any other option ordered such as cord with plug requires voltage to be specified). Not available with 9000LM, 12000LM, 15000LM, or 18000LM.
IE20WCPHE	Available with MVOLT, 120, 208, 240, or 277. (120, 208, 240, or 277 when any other option ordered such as cord and plug requires voltage to be specified). Not available for 9LM, 12LM, 15LM and 18LM. Not available with NLTAIR2 KO and Cordset together. Not for use with THUN.
IMP	Not available with battery options, NLTAIR2 KO options, PIRHKO or APIRHKO options, ETS, or NLTAIRER2 APIRHKO options. Sensors will be fixture pre-wired to fixture. Not for use with THUN mounting option.
Individual Controls (LSXR)	Comes standard with SPD. SSE PIRAKO not available as a Design Select option when ordered with 70CRI option. This sensor configuration is suitable for minimum ambient temperature of 14°F (-10°C). Not available with other controls.
JP	Consult table on page 7 for details.
NLTAIR2 APIR, APIRH, or APIRA	Not available with NLTAIRER2 when ordered with 9000LM, 12000LM, 15000LM or 18000LM lumen packages (ER option utilizes ETS). Not available with HVOLT, 347, or 480 when ordered with a battery.
NLTAIR2 KO	Comes standard with SPD.
NLTAIREM2 KO	Comes standard with SPD. Not available with Emergency battery options.
NLTAIRER2 KO	Comes standard with SPD. Not available with emergency battery options.
OCS	Must specify voltage. Dry Location listed only.
OCS4C	Dry location listed only. Use when unswitched hot is required for battery pack options.
SPD	10kV surge protector standard with HVOLT, 347, 480, ETS, any NLTAIR2, and battery options (on the unswitched, battery hot).
THUN J2	Order quantity required in multiples of two. 9000LM – 18000LM requires one per fixture, 24000LM – 60000LM requires two per fixture. Not for use with IMP or battery pack options.
CNP5CDW	When ordered with a battery pack, 2470P is required.

‡ Design Select Ordering Restrictions	
Option Value	Ordering Restrictions
CPTLW	Not on program when combined with 208V, 240V, or 347V
Individual Controls	Not on DS program when ordered as SSE PIRAKO with 70CRI.
OCS, OCS4C (all lengths)	Not on program when combined with 120V, 208V, 240V, or 347V

CORD SET ORDERING INFORMATION

Plug Option	Plug type	Amperage**	Gauge	# of conductors	Color	Location	Length*****
CNP Cord Only CP Cord with Plug	(blank) No Plug Option (for Cord Only option) TL Locking Type SB Straight blade*	(blank) 15 amps 20A 20 amps***	(blank) 18 gauge standard	(blank) 3 conductors (blk/wht/grn) 4C 4 conductors; Use with Battery option when unswitched hot is needed 5CD **** 5 conductors; Use with dimming driver when dimming leads are desired (Not for use with dimming sensors)	W White	(blank) Damp Location	(blank) 6 feet 3FT 3 feet 10FT 10 feet 12FT 12 feet 15FT 15 feet 20FT 20 feet

* Straight blade on available with 120, 208, 240, and 277 volt.
 ** Amperage is only configurable for cords with plugs.
 *** 20A required with 347 and 480 volt.
 **** Not available with plugs.
 ***** Available in 1' increments from 1 to 30 feet.

NEMA PLUG CONFIGURATION

Voltage	Straight blade	Twist-lock 15 amp plug	Twist-lock 20 amp plug
120	5-15P	L5-15P	L5-20P
208/240	6-15P	L6-15P	L6-20P
277	7-15P	L7-15P	L7-20P
347	X	X	L24-20P
480	X	X	L8-20P

EMBEDDED LUMINAIRE TECHNOLOGY GUIDE

Control type	Sensor nomenclature	Sensor used (click part number to link to sensor spec sheet)	Out of the box settings					Notes	
			Unoccupied time until dim/off	Dim to off time delay	Occupied dim level	Unoccupied dim level	Daylighting set point		
Sensor Switch embedded controls	SSE PIRHKO	LSXR 6	10M	n/a	10V/100%	n/a	n/a		
	SSE PIRKO	LSXR 10	10M	n/a	10V/100%	n/a	n/a		
	SSE PIRAKO	LSXR 50	10M	n/a	10V/100%	n/a	n/a		
	SSE PIRHKO HL	LSXR 6 HL	10M	2.5M	10V/100%	1V/10%	n/a		
	SSE PIRKO HL	LSXR 10 HL	10M	2.5M	10V/100%	1V/10%	n/a		
	SSE PIRAKO HL	LSXR 50 HL	10M	2.5M	10V/100%	1V/10%	n/a		
	SSE PIRHKO P	LSXR 6 P	10M	n/a	10V/100%	n/a	4FC		
	SSE PIRKO P	LSXR 10 P	10M	n/a	10V/100%	n/a	4FC		
	SSE PIRAKO P	LSXR 50 P	10M	n/a	10V/100%	n/a	4FC		
	SSE APIRHKO	LSXR 6 ADC	10M	n/a	10V/100%	1V/10%	4FC	ADC only dims based on photocell	
	SSE APIRKO	LSXR 10 ADC	10M	n/a	10V/100%	1V/10%	4FC	ADC only dims based on photocell	
	SSE APIRAKO	LSXR 50 ADC	10M	n/a	10V/100%	1V/10%	4FC	ADC only dims based on photocell	
	SSE APIRHKO ANL	LSXR 6 ANL	10M	n/a	10V/100%	1V/10%	4FC	ANL dims by occupancy and photocell but only turns off due to photocell	
	SSE APIRKO ANL	LSXR 10 ANL	10M	n/a	10V/100%	1V/10%	4FC	ANL dims by occupancy and photocell but only turns off due to photocell	
SSE APIRAKO ANL	LSXR 50 ANL	10M	n/a	10V/100%	1V/10%	4FC	ANL dims by occupancy and photocell but only turns off due to photocell		
nLight AIR2 embedded controls	NLTAIR2 APIRH	RMSOD 45 180D G2	7.5M	5M	10V/100%	3V/30%	5FC		
	NLTAIREM2 APIRH	RMSOD 45 EM 180D G2	7.5M	5M	10V/100%	3V/30%	5FC		
	NLTAIR2 APIRKO	RLSXR 10 WH G2	7.5M	2.5M	10V/100%	1V/10%	50FC		
	NLTAIR2 APIRHKO	RLSXR 6 WH G2	7.5M	2.5M	10V/100%	1V/10%	50FC		
	NLTAIR2 APIRAKO	RLSXR 50 WH G2	7.5M	2.5M	10V/100%	1V/10%	50FC		
	NLTAIREM2 APIRKO	RLSXR 10 EM WH G2	7.5M	2.5M	10V/100%	1V/10%	50FC		
	NLTAIREM2 APIRHKO	RLSXR 6 EM WH G2	7.5M	2.5M	10V/100%	1V/10%	50FC		
	NLTAIREM2 APIRAKO	RLSXR 50 EM WH G2	7.5M	2.5M	10V/100%	1V/10%	50FC		
	NLTAIRER2 APIRKO	RLSXR 10 WH G2	ETS DR	7.5M	2.5M	10V/100%	1V/10%	50FC	
	NLTAIRER2 APIRHKO	RLSXR 6 WH G2	ETS DR	7.5M	2.5M	10V/100%	1V/10%	50FC	
	NLTAIRER2 APIRAKO	RLSXR 50 WH G2	ETS DR	7.5M	2.5M	10V/100%	1V/10%	50FC	
	NLTAIR2	RIO ZT 90 G2		n/a	n/a	80%	n/a	n/a	
	NLTAIR2 KO	RPP20 D EFP G2		n/a	n/a	100%	n/a	n/a	
	NLTAIREM2 KO	RPP20 D EM EFP G2		n/a	n/a	100%	n/a	n/a	
NLTAIRER2 KO	RPP20 D ER EFP G2	ETS DR	n/a	n/a	100%	n/a	n/a		

PHOTOMETRICS

See www.lithonia.com.

PERFORMANCE TABLE

CPHB SEF	Glare Control Lens, Medium Distribution			
	Lumen Package	Wattage	Lumen Output	LPW
Delivered Lumens 4000K, 80CRI	9000LM	61	9,123	150
	12000LM	87	12,273	141
	15000LM	102	15,343	150
	18000LM	133	18,199	137
	24000LM	174	24,873	143
	30000LM	210	29,825	142
	36000LM	235	36,289	163
	48000LM	324	48,342	153
	60000LM	421	58,946	140

Delivered Lumens 5000K, 80CRI	9000LM	61	9,183	150
	12000LM	88	12,354	140
	15000LM	105	15,444	147
	18000LM	133	18,319	138
	24000LM	174	25,037	144
	30000LM	210	30,081	143
	36000LM	235	36,529	155
	48000LM	324	48,661	150
	60000LM	421	59,452	141

*Values shown are at 120V.

SCALING FACTOR TABLES

Multipliers	
ND	1.037
WD	1.004
WGX	0.95

CPHB HEF	Glare Control Lens, Medium Distribution			
	Lumen Package	Wattage	Lumen Output	LPW
Delivered Lumens 4000K, 80CRI	9000LM	55	8,861	161
	12000LM	75	12,056	161
	15000LM	96	14,875	155
	18000LM	127	18,936	149
	24000LM	150	23,740	158
	30000LM	196	29,644	152
	36000LM	210	35,409	169
	48000LM	292	47,480	163
	60000LM	378	59,274	157

Delivered Lumens 5000K, 80CRI	9000LM	55	9,002	164
	12000LM	75	12,248	163
	15000LM	96	15,111	157
	18000LM	127	19,236	151
	24000LM	150	24,117	161
	30000LM	196	30,115	154
	36000LM	210	35,971	171
	48000LM	292	48,234	165
	60000LM	378	60,215	159

CPHB CHARACTERISTICS

Lumen package	Wattage								Length	Width	Depth	Weight	Comparable light source
	Standard Efficiency (SEF)				High Efficiency (HEF)								
	120V	277V	347V	480V	120V	277V	347V	480V					
9000LM	61	60	60	60	55	54	54	54	14.4 (36.6)	11.5 (29.2)	2.3 (5.8)	5 (2.2)	100W MH, 4-lamp T8 NBF
12000LM	88	88	88	87	75	74	74	74	14.4 (36.6)	11.5 (29.2)	2.3 (5.8)	5 (2.2)	175W MH, 4-lamp T8 HBF, 2-lamp T5HO
15000LM	105	104	104	103	96	95	95	94	14.4 (36.6)	11.5 (29.2)	2.3 (5.8)	5 (2.2)	200W MH, 6-lamp T8 NBF
18000LM	133	132	144	144	127	126	138	138	14.4 (36.6)	11.5 (29.2)	2.3 (5.8)	6.5 (2.9)	250W MH, 6-lamp T8 HBF, 4-lamp T5HO
24000LM	174	174	173	173	150	149	149	149	22.8 (57.9)	11.5 (29.2)	2.3 (5.8)	8 (3.6)	400W MH, 6-lamp T5HO
30000LM	210	209	208	208	196	194	194	194	22.8 (57.9)	11.5 (29.2)	2.3 (5.8)	8 (3.6)	575W MH, 10-lamp T8 HBF
36000LM	235	235	234	234	210	208	208	208	44 (111.8)	11.5 (29.2)	2.3 (5.8)	14 (6.35)	750W MH, 8-lamp T5HO
48000LM	324	322	320	320	289	287	286	285	44 (111.8)	11.5 (29.2)	2.3 (5.8)	14 (6.35)	875W MH, 10-lamp T5HO
60000LM	421	421	419	419	374	372	371	370	44 (111.8)	11.5 (29.2)	2.3 (5.8)	14 (6.35)	1000W MH

*Dimensions & weights shown for standard product configurations without optional components

PROJECTED LUMEN MAINTENANCE

Operating hours	10,000	20,000	30,000	40,000	50,000	60,000	70,000	80,000	90,000	100,000
Lumen maintenance factor	0.98	0.96	0.93	0.91	0.89	0.87	0.85	0.83	0.81	0.79

BATTERY INFORMATION

EMERGENCY BATTERY PACK OPTIONS

Nomenclature	Part Number	Utilizes BPK option	Field installable (remote mount only)
E10W (MVOLT only)	ILD 10 MVOLT LQD 10-55 PLENUMSS	Yes	Yes
E10WCP (MVOLT only)	PS1055CP	Yes	Yes
E15WMCP (MVOLT only)	PS1555MCP	Yes	No
IE10WMCP (HVOLT only)	ILBHI CP10 HE SD LCSTICK	Yes	No
IE15WMCP (HVOLT only)	ILBHI CP15 HE SD LCSTICK	Yes	No
IE20WCPHE (MVOLT only)	ILB CP20HE SD R	No	Yes


EMERGENCY LUMENS GCL, MD (5000K, 80CRI)			
	Lumen Package	E10W/ E10WCP	E15WMCP
SEF	9000	1784	2738
	12000	1778	2729
	15000	1734	2701
	18000	1796	2744
	24000	1847	2845
	30000	1884	2868
	36000	1890	2915
	48000	1888	2912
	60000	1872	2853

EMERGENCY LUMENS GCL, MD (5000K, 80CRI)			
	Lumen Package	E10W/ E10WCP	E15WMCP
HEF	9000	1916	2911
	12000	1914	2909
	15000	1919	2914
	18000	1916	2898
	24000	1966	2984
	30000	1945	2952
	36000	2058	3125
	48000	2057	3124
	60000	2065	3137


Emergency Batteries & Cord Sets - WIRING

When battery is ordered with a 3-conductor cord set and 24/7 operation

Ideal for use with battery + SENSOR to control fixture on/off based on occupancy. Order option 247OP to receive wired for this scenario. When 247OP is ordered driver black (Hot) and battery red (Hot) will be wired together inside driver channel.



When battery is ordered with a 4-conductor cord set...




Emergency Batteries & Cord Set Notes

- When a battery is ordered with a 3 conductor cord set, 247OP option is required.
- The 3 conductor cord set will include the hot (BLK), neutral (WHT), and ground (GRN) conductors. 24/7 operation means the design intent is for the fixture to always receive power and never be switched off. This ensures the battery is always being charged. When 247OP is ordered with a 3/c cord set, the red battery hot will be wired to the normal hot inside the driver channel, and the new hot wire lead will exit the fixture with the ground and neutral wires. Consult local codes to determine if this is allowable.
- When a battery is ordered with a 4 conductor cord set...
 - The unswitched hot will be included in the cord set as a separate conductor (RED).


MOUNTING ACCESSORIES




ZACVH
(mounts in holes on fixture channel)




End View: CPHB 9000LM - 60000LM




Side View: 9000LM, 12000LM, 15000LM, 18000LM




Side View: 24000LM, 30000LM




Side View: 36000LM, 48000LM, 60000LM





CPHB 9000LM - 18000LM WITH E10WCP/E15WMCP




CPHB 9000LM - 60000LM WITH E10WCP/E15WMCP




CPHB 24000LM - 30000LM WITH E10WCP/E15WMCP



CPHB 24000LM - 30000LM WITH IE20WCPHE




CPHB 36000LM - 60000LM WITH E10WCP/E15WMCP



CPHB 36000LM - 60000LM WITH IE20WCPHE

JOB PACK DETAILS



*Representative of Job Pack design for 14" standard units.

Series	Performance	Lumens	Standard Fixture	Cord Set or RELOC® JP	Wireguard JP	Sensor JP
CPHB	SEF/HEF	9000LM	144	144	144	90*
		12000LM				
		15000LM				
		18000LM				
		24000LM	96	96	96	60*
		30000LM				
		36000LM	45*	30*	30*	30*
		48000LM				
		60000LM				

*Traditional Job Pack

Breakout Example:		
Ordered Line:	Qty: 200	CPHB 24000LM SEF GCL MD MVOLT GZ10 40K 80CRI CNPW DWH JP
		*Above configuration shows 96 units for Job Pack
Breakout Line 1:	Qty: 192	CPHB 24000LM SEF GCL MD MVOLT GZ10 40K 80CRI CNPW DWH JP96
		*Will have 2 pallets of 96 units each in job packs
Breakout Line 2:	Qty: 8	CPHB 24000LM SEF GCL MD MVOLT GZ10 40K 80CRI CNPW DWH
		*Balance will ship in unit cartons

Note: If quantity ordered is less than Job Pack quantity for that configuration, the breakout line will default to unit packs.

STANDARD SENSOR

	Standard Sensor or Control Device (commonly used with Battery Pack Option)	EM Solution (Used when switching single incoming hot to generator power)	ER Solution (Used when switching to generator power via a 2nd hot lead)
Emergency Operation Scenarios	Emergency Lighting Strategy	*Luminaire-integral battery pack and emergency driver *Generator transfer device	*Diesel genset emergency backup supply *Slow transfer inverter (>30ms) emergency backup supply
	Recommended Control Device Option	*Not specifically listed for emergency use. *Wired such that a separately listed emergency device provides emergency lighting power and/or control during loss of normal power scenarios.	*UL 924 listed *EM devices will remain at their high-end trim and ignore wireless lighting control commands, such as in the event of a normal power failure, unless a normal-power-sensed (NPS) broadcast is received at least every 8 seconds. * Using the CLAIRITY+ mobile app, EM devices must be associated with a group that includes a normal power sensing device to receive NPS broadcasts. *Only non-emergency rPP20, rLSXR, rSBOR, rSDGR, and nLight AIR luminaires with version 3.4 or later firmware can provide normal power sensing for EM devices. See specification sheets for control devices and luminaires for more information on options that support normal power sensing.

Function	Sequence of Operations	Standard Sensor or Control Device	EM Solution (Generator / Inverter powered with 1 hot)	ER Solution (Generator / Inverter on separate emergency circuit – 2 hots)	CPHB Standard Sensor Settings					
					Vacancy Time Out	Dim to Off Time Delay	High Trim	Low Trim	Photocell Set Point	
On/Off	Lights turn on when motion detected; Upon vacancy, Lights turn off after timeout.	PIRHKO	-	PIRHKO ER	10 min	-	-	-	-	
High/Low (Off)	Lights turn on to high trim when presence is detected; Upon vacancy, the lights dim to low trim after timeout and turn off after "Dim To Off" Time Delay. For High/Low (Never Off) function, bypass the relay by bringing power directly into driver rather than wiring hot through LSXR device.	PIRHKO HL	-	PIRHKO HL ER	10 min	2.5 min	100%	10% (Driver Low)"	-	
Photocell	Lights turn on unless ambient light level is above set point; If ambient light levels in the space exceed the photocell set point, lights will turn off even during occupancy.	PIRHKO P	-	PIRHKO P ER	-	-	-	-	4 fc	
Dimming + Photocell	Lights turn on when presence is detected unless ambient light level is above set point; Upon vacancy, the lights dim to low trim, then turn off after timeout; During occupancy, automatically raise and lower electric light level to maintain set point and turn off, depending on ambient light.	APIRHKO	-	APIRHKO ER	10 min	2.5	-	-	4 fc	
Dimming + Photocell + High/Low	Lights turn on when presence is detected unless ambient light level is above set point; Upon vacancy, lights dim to low trim after timeout and remain at low trim until presence is detected; Automatically raise and lower electric light level to maintain set point during occupancy and during vacancy keeps lights at low trim if ambient light is not sufficient.	APIRHKO ANL	-	APIRHKO ANL ER	10 min	-	100%	10%	4 fc	
Note: For 360° integral Low Mount sensors, replace "6" in nomenclature with "10". Ex. LSXR10 P. For High Aisle Mount sensors, replace "6" with "50".										


nLight AIR Wireless Sensors	Dimming + Photocell + Occupancy	Wirelessly programmable network sensor – On/Off control with dimming, occupancy detection, and daylight harvesting (Sensor embedded in fixture)	NLTAIR2 APIRH	NLTAIREM2 APIRHKO	NLTAIRER2 APIRHKO	7.5 min	-	100%	30%	50 fc
	Dimming	Wirelessly programmable On/Off control with dimming – no sensor (Device embedded in fixture)	NLTAIR2	NLTAIREM2	NLTAIRER2	-	-	100%	10% (driver low)	-
Note: For 360° integral Low Mount sensors, replace "45" in nomenclature with "7". EM sensors/controls are KO-mounted; all others integral. RPP20 D EM de-rates fixture to Damp Location.										

***All ER solutions include standard sensor or control device with a factory-installed Iota ETS#-DR (UL924 bypass device). This device is integral to the fixture and will include a hot and neutral lead for the dedicated emergency circuit. MVOLT, 120-277 only. ER solutions are not available with the IMP option.**

Fixture Mount Occupancy Sensor
(see www.AcuityControls.com for additional information)


- Three interchangeable lens options to satisfy multiple mounting heights and coverage pattern requirements.
- Integrated mounting bracket drops lens down 3" from chase nipple.
- Single or dual relay versions — designed with robust protection from the harsh switching requirements of T5 and LED loads.
- Photocell and 0-10VDC dimming options.
- No PIR field calibration or sensitivity adjustments required.
- Sensor ambient temperature rating of 14°F (-10°C) to 131°F (55°C).

New sensor nomenclature.	LSXR configuration	Comparable CMRB sensor	Old style sensor nomenclature
For shortest lead times use one of the following LSXR configurations			
	LSXR50 / LCOZU	CMRB 50	MSI
	LSXR50 HL / LCHOSZU	CMRB 50 D	MSID
	LSXR50 P / LCPZU	CMRB 50 P	MSIPED
	LSXR6 / LAOZU	CMRB 6	MSI360
	LSXR6 HL / LAHOSZU	CMRB 6 D	MSI360D
	LSXR6 P / LAPZU	CMRB 6 P	MSI360PED




LSXR COVERAGE PATTERNS

HIGH MOUNT 360° LENS (#6)




- Best choice for 15 to 45 ft (4.57 to 13.72 m) mounting heights
- 15 to 20 ft (4.57 to 6.10 m) radial coverage overlaps area lit by a typical high bay fixture
- Excellent detection of large motion (e.g. walking) up to a 35 ft (10.76 m) mounting height
- Excellent detection of extra large motion (e.g. forklifts) up to a 45 ft (13.72 m) mounting height


LOW VIEW



HIGH VIEW




HIGH MOUNT AISLEWAY LENS (#50)




- Provides a bi-directional coverage pattern ideal for warehouse racking
- 1.2x mounting height equals approximate detection range in either direction
- Typical 40 ft (12.19 m) mounting detects 50 ft (15.24 m) in either direction
- Superior aisleway coverage compared to a masked 360° lens


SIDE VIEW



TOP VIEW




LOW MOUNT 360° LENS (#10)




- Best choice for large motion detection (e.g. walking)
- 360° conical shaped pattern
- Provides ~24 ft (7.32 m) radial coverage (~2000 ft²) when mounted at 9 ft (2.74 m)
- 7 to 15 ft (2.13 to 4.57 m) mounting heights provide 16 to 36 ft (4.88 to 10.97 m) radial coverage
- Detection range improves when walking across beams compared to into beams


SIDE VIEW



TOP VIEW




nLIGHT AIR CONTROLS – NLTAIR2 APIRKO, APIRHKO, OR APIRAKO




NLTAIR2 APIRKO, APIRHKO, or APIRAKO COVERAGE PATTERNS

HIGH MOUNT 360° LENS (#6)




- Best choice for 15 to 45 ft (4.57 to 13.72 m) mounting heights
- 15 to 20 ft (4.57 to 6.10 m) radial coverage overlaps area lit by a typical high bay fixture
- Excellent detection of large motion (e.g. walking) up to a 35 ft (10.76 m) mounting height
- Excellent detection of extra large motion (e.g. forklifts) up to a 45 ft (13.72 m) mounting height


LOW VIEW



HIGH VIEW




HIGH MOUNT AISLEWAY LENS (#50)




- Provides a bi-directional coverage pattern ideal for warehouse racking
- 1.2x mounting height equals approximate detection range in either direction
- Typical 40 ft (12.19 m) mounting detects 50 ft (15.24 m) in either direction
- Superior aisleway coverage compared to a masked 360° lens


SIDE VIEW



TOP VIEW




LOW MOUNT 360° LENS (#10)




- Best choice for large motion detection (e.g. walking)
- 360° conical shaped pattern
- Provides ~24 ft (7.32m) radial coverage (~2000ft2) when mounted at 9 ft (2.74 m)
- 7 to 15 ft (2.13 to 4.57 m) mounting heights provide 16 to 36 ft (4.88 to 10.97 m) radial coverage
- Detection range improves when walking across beams compared to into beams

SIDE VIEW




TOP VIEW



NLTAIR2 APIR, APIRH, OR APIRA

- 100% digital PIR detection
- Combined daylight and occupancy sensor
- Fully dimmable via digital or analog dimming protocols, providing the right amount of light for the application and to optimize energy savings
- Optional UL 924 emergency functionality via EM option, which eliminates wiring for sensing normal power




COVERAGE PATTERN

Lens rotates 15 deg to enable adjustment. Initial detection will occur earlier when walking across sensor's field of view than when walking directly at sensor.


7 – MINI LOW-BAY 360°

- Recommended for walking motion detection from mounting heights between 8 ft (2.44 m) and 20 ft (6.10 m)
- Initial detection of walking motion along sensor axis at distances of 2x the mounting height up to 15 ft (4.57 m) and 1.75x up to 20ft (6.10 m).
- Provides 12 ft (3.66 m) radial detection of small motion when mounted at 9 ft (2.74 m)




30 – UNIVERSAL 360°

- Provides excellent detection of large motion (e.g. walking) when mounted between 15 to 40 ft (4.57 to 12.19 m)
- 15 to 20 ft (4.57 to 6.10 m) radial coverage overlaps area lit by a typical high bay fixture
- Recommended for fixtures that have a 1:1 spacing to mounting height ratio or less (e.g. fixtures 30' on center or less @ a 30' mounting height.)



45 – HIGH MOUNT 360°

- Optimized full coverage pattern for 10 – 40 ft. (3.1 – 12 m)
- Reliable detection of large motion (e.g. pedestrian walking traffic) up to 30 ft. (9.1 m) mounting height
- Reliable detection of extra-large motion (e.g. forklift traffic) up to 40 ft. (12 m) mounting height



IMP – Integrated Modular Plug

- The integrated modular plug (IMP) option allows the installer to plug and play a multitude of accessories.
- Cord sets connect quickly to any fixture with IMP option.
- IMP accessories include occupancy sensors, photocells, X-point relays.

IMP compatible cord sets ¹	
CS1WIMP	Straight plug, 120V
CS3WIMP	Twist-lock, 120V
CS7WIMP	Straight plug, 277V
CS11WIMP	Twist-lock, 277V
CS25WIMP	Twist-lock, 347V
CS93WIMP	600V SE00W white cord, no plug
CS97WIMP	Twist-lock, 480V

Ordering Example

Order As: Qty 1 – IBG 12000LM SEF AFL GND 120 GZ10 40K 80CRI IMP CP5BW DWH

Ships As: Qty 1 – IBG 12000LM SEF AFL GND MVOLT GZ10 40K 80CRI DWH

Qty 1 – CS1WIMP

Notes

¹ Cord set required for fixture operation. All cord sets are 18/3, 6' white.

RRL – RELOC®-Ready Luminaire

- RRL connectors to be used with the OnePass system.
- Load side of connector factory installed to luminaire.
- 4-pole mating connector with push-in terminations allows for simple installation.
- Touch-safe design on both halves meets UL/CSA requirement.
- Wiping contact design allows safe disconnect under load.



ORDERING INFORMATION Lead times will vary depending on options selected. Consult with your sales representative. **Example: RRLA**

Series	Wiring instructions
RRL RELOC®-ready luminaire	<p>A Hot conductor wired to position #1 (phase A); non-dimming</p> <p>B Hot conductor wired to position #2 (phase B); non-dimming</p> <p>AE Hot conductor wired to position #1 (phase A), hot conductor #2 wired to position #2 (phase B); non-dimming¹</p> <p>C12S Hot conductor in position #1 (phase A), low voltage conductor #1 in position #2, low voltage conductor #2 in position #3; dimming²</p>

Compatible RELOC® Cables for Industrial Luminaires (ordered and shipped separately)

(click to view RELOC product page for more information)



Notes

- ¹ AE commercial fixtures should disconnect the TSPL before unplugging the RRL so it does not go into discharge mode. Requires fixture to have battery option.
- ² C12S option is used with the OnePass for 0-10V/DALI applications. Not for use with dimming sensors.