LBR Series

Retrofit | Remodel Downlight

- Switchable CCTs and lumens
- Aperture sizes including 4", 6", 8", and 10"
- Glare control with deep source regression
- Up to 114 LPW
- Available with battery pack, IOTA emergency transfer system (ETS), 347V step-down transformer and optional wet location (IP55) listed
- Configurations available in Contractor Select™
- nLight® wired or wireless lighting controls and SensorSwitch™ JOT single room controls
- 10% and 1% dimming, MVOLT 120-277V, 0-10V and phase dimming in an all-in-one driver or a separate DALI driver

BATTERY BACKUP

Make the Switch to LBR.

Switchable CCTs & Lumens



CCTs
- 3000K
- 3500K
- 4000K
- 5000K

Lumen Packages
- 500, 750, 1000LM
- 1000, 1500, 2000LM
- 2000, 2500, 3000LM
- 4000, 4500, 5000LM

Deep Source Regression



55° Cutoff

Options

Three distributions and square trims are available



Smash plates and goof rings available for extra flexibility

Available with new construction frame and quick disconnection options

Start Saving

Energy Savings
Reduce between 50-80% energy consumption compared to traditional sources

Low Labor Costs
Minimum install and cleanup time

Environmental Impact
Last up to 25 times longer than traditional sources

Lighting Controls

SensorSwitch™ JOT is a wireless, app free solution for single room controls

The nLight® platform offers wired or wireless networked lighting control solutions

Visit www.lithonia.com for more information

One Lithonia Way, Conyers, Georgia 30012 | Phone: 800.705.7378 | www.acuitybrands.com
©2021 Acuity Brands Lighting, Inc. All rights reserved. | LL_398514.30_0721