

# Juno® Canless 2in Wafer Downlights

### Tiny but Mighty with Ultimate Flexibility

2in Canless Wafer Downlights have an innovative, slim design that installs quickly and easily into ceiling spaces where most traditional recessed housings do not, no housing required to install. These miniature Wafer downlights provide an all-in-one design featuring switchable white color temperature and adjustable lumen output technology making them perfect for accent, task or general downlighting applications. This technology gives distributors, contractors, and homeowners the ultimate in flexibility by providing the equivalent of 15 static fixtures in one.

#### **Features Include:**

- Style Available in 3 styles: Flat, Deep Regressed Smooth and Deep Regressed Baffle.
   Plus, trim inserts available in matte black, brushed nickel, & oil-rubbed bronze to match any desired aesthetic.
- Canless Design Installs directly below the ceiling for easy retrofit, remodel, or new construction application, no housing required. New construction mounting frame available.
- Easy Electrical Connections Driver box designed with a large wiring compartment to make electrical connections a breeze.
- Switchable Color Temperature Switch located directly on the fixture allowing you
  to choose between 5 color temperature settings (2700K Warm White, 3000K, 3500K,
  4000K, and 5000K Daylight), 90CRI.
- Adjustable Lumen Output Switch located directly on the fixture allowing you to choose between 3 lumen outputs (Low, Medium, High) for ultimate application flexibility.
- IC Rated Fixture and driver box can be installed in direct contact with insulation.















Deep Regressed Smooth



Deep Regressed Baffle





Choose desired color temperature during install.

Too warm or too cool? Simply toggle the switch to your desired setting (2700K Soft White up to 5000K Daylight).

Flexibility at your fingertips

Choose desired lumen output during install. Too dim or too bright? Simply toggle the switch to your desired setting (low, medium, or high).

#### **Ultimate Application Flexibility - Offering Task, General, and Accent Lighting from the Same Product**







**General Lighting** 



**Accent Lighting** 

### **Ordering Information**

Catalog Number	UPC	Description	Replaces Up to	Lumens (30K)	Nominal Input Watts	CCT	CRI	Voltage	Finish	Dimming Protocol	Pallet Quantity
WF2 RD AL025 SWW5 90CRI 120 MW M6	00197589570755	2" Flat LED Downlight	65W Incandescent	517 689 862	10W	2700K/3000K/ 3500K/4000K/5000K	90	120V	Matte White	Forward/ Reverse Phase	540
WF2 DREG B AL025 SWW5 90CRI 120 MW M6	00197589570779	2" Deep Regressed Baffle LED Downlight	65W Incandescent	544 725 907	10W	2700K/3000K/ 3500K/4000K/5000K	90	120V	Matte White	Forward/ Reverse Phase	540
WF2 DREG SM AL025 SWW5 90CRI 120 MW M6	00197589570816	2" Deep Regressed Smooth LED Downlight	65W Incandescent	544 725 907	10W	2700K/3000K/ 3500K/4000K/5000K	90	120V	Matte White	Forward/ Reverse Phase	540

Color Finish Trim Inserts Available - See Spec Sheets for full details.

## **Stock at your fingertips**



Inventory available through your preferred authorize distributor or retailer. For larger projects, we have products in stock and available for same-day shipments from our North American distribution centers.



















