


Catalog Number
Notes
Type

APPLICATION GUIDE: STANDARD SPECIAL SIGNAGE


Lithonia Lighting offers special signage signs to suit many applications. The Signature and Quantum families highlighted below are illuminated with energy-efficient, long-life Light Emitting Diodes (LEDs).

WARRANTY — This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at: www.acuitybrands.com/support/warranty/terms-and-conditions


Note: Actual performance may differ as a result of end-user environment and application. Specifications subject to change without notice.



SW01




SW02



SW03



SW04



SW05




SW06




SW07




SW08



SW09



SW10




SW11




SW12



SW13




SW14




SW15




SW16



SW17



SW18



SW19

CUSTOM SIGNAGE

Example: LQM P W 3 R 120/277 SW02
Break out as: LQM P W 3 R 120/277 SW00 M6
 SPLQM W R SW02 AOFRSU S31

ORDERING INFORMATION

Lead times will vary depending on options selected. Consult with your sales representative.

Family ^{1,2}	Face type	Housing color	Number of faces	Letter color	Input voltage	Operation
LQM Quantum® thermoplastic sign	P Panel	W White	3 Single face with extra faceplate and color panel	R Red G Green	120/277 Dual voltage	(blank) AC only

Notes

- 1 See spec sheet [LQM](#) for complete fixture specifications. Not available with other options or battery back-up (EL N).
- 2 Not available with single (1) or double (2) face.

Example: LE P W 1 R SW02
Break out as: LE P W 1 R SW00
 SPLEW R SW02 AOFRSU

ORDERING INFORMATION

Lead times will vary depending on options selected. Consult with your sales representative.

Family ¹	Face type	Housing color	Number of faces	Letter color	Input voltage	Operation
LE Signature® die-cast aluminum sign	P Panel	(blank) Matte black, brushed aluminum face W White	1 Single face 2 Double face	R Red G Green	(blank) 120 thru 277V, 50/60hz	(blank) AC only EL N Nickel-cadmium battery

Notes

- 1 See spec sheet [LE](#) for complete fixture specifications. Not available with other options.

Special wording							
SW01	AREA OF REFUGE ¹	SW06	DARK ROOM IN USE ^{1,2}	SW11	MAGNET IN USE ^{1,2}	SW15	SALIDA ⁴
SW02	AREA OF RESCUE ¹	SW07	EXIT Arabic/English ^{3,4}	SW12	NO EXIT ⁴	SW16	X-RAY IN USE ^{1,2}
SW03	AREA OF RESCUE ASSISTANCE ¹	SW08	EXIT with access pictogram ⁴	SW13	ON AIR ^{1,2}	SW17	Handicap Symbol ¹
SW04	AREA OF RESCUE ASSISTANCE with access pictogram ¹	SW09	IN USE ^{1,2}	SW14	ROOM IN USE ^{1,2}	SW18	MRI IN USE ^{1,2}
SW05	BEAM IN USE ^{1,2}	SW10	LASER IN USE ^{1,2}			SW19	BEAM ON ^{1,2}

Notes

- 1 UL48 listing as an electric sign only.
- 2 Not available with EL N operation.
- 3 Only available in red letters.
- 4 Not available with UL924 listing.

MAINTENANCE

All life safety equipment, including emergency lighting for path of egress must be maintained, serviced, and tested in accordance with all National Fire Protection Association (NFPA) and local codes. Failure to perform the required maintenance, service, or testing could jeopardize the safety of occupants and will void all warranties.