



| |
|----------------|
| Catalog Number |
| Notes |
| Type |

Contractor Select™

CNY LED ALO

Canopy Luminaire
Adjustable+Switchable+Photocell
+Occupancy Sensor

The Lithonia Lighting CNY LED ALO canopy luminaire is a versatile, energy-efficient solution for surface-mount applications for walkways, overhangs, and parking garages. Adjustable switch panel easily changes lumen output, color temperature, integrated photocell, and integrated motion sensor. The low profile frosted lens creates a visually comfortable illumination and even distribution.

FEATURES:

- 3 power levels deliver 5,000 - 10,000 lumens.
- Switchable CCT (30K/40K/50K) offers warm, cool, and daylight in a single fixture
- Integrated On/Off photocell
- Integrated occupancy sensor can be turned on, off, or set to 10% dim
- Install by surface mount, junction box, or pendant mount
- IK08 Impact resistant polycarbonate frosted lens
- IP65 rated, die cast aluminum housing



Adjustable Lumen Output
ALO



Switchable CCT
SWW2



Integrated Photocell



Integrated Motion Sensor



| Catalog Number | Adjustable Lumen Output ALO | | | Switchable CCT SWW2 | Photocell Operation | Occupancy Sensor | Input Voltage | CRI | Finish |
|--------------------------------------|-----------------------------|--------------|---------------|--------------------------------|--------------------------------------|--|---------------|-------|-------------|
| CNY LED ALO SWW2 UVOLT PE PIR DDB M2 | 5,000 Lumens | 7,500 Lumens | 10,000 Lumens | Switchable 3000K, 4000K, 5000K | Included Standard, Selectable On/Off | Included Standard, Selectable On/Off/10% Dim | 120-347V | 80CRI | Dark Bronze |
| CNY LED ALO SWW2 UVOLT PE PIR WH M2 | 5,000 Lumens | 7,500 Lumens | 10,000 Lumens | Switchable 3000K, 4000K, 5000K | Included Standard, Selectable On/Off | Included Standard, Selectable On/Off/10% Dim | 120-347V | 80CRI | White |

CNY Stock Options

| Catalog Number | UPC | Ci Code | Number of fixtures per pallet | Traditional Replacement |
|--------------------------------------|----------------|---------|-------------------------------|-------------------------|
| CNY LED ALO SWW2 UVOLT PE PIR DDB M2 | 00197589495041 | *284HU8 | 180 | Up to 250W HID |
| CNY LED ALO SWW2 UVOLT PE PIR WH M2 | 00197589495126 | *284HUH | 180 | Up to 250W HID |

Accessories: Order as separate catalog number.

| | |
|----------------|--|
| CNYBCP DDB | 14 Inch x 14 Inch Beauty Cover Plate |
| CNYEK E7WC M12 | Field installable emergency battery; 7W, UVOLT compatible, Minimum operating temp of 0°C |

Lumen Output:

Lumen values are from photometric tests performed in accordance with IESNA LM-79-08. Data is considered to be representative of configurations shown within the tolerances described within LM-79.

| Lumen Output | Input Wattage | CCT/80CRI | Delivered Lumens | Lumens Per Watt |
|--------------|---------------|-----------|------------------|-----------------|
| 5,000 | 34 | 3000K | 4709 | 139 |
| | | 4000K | 4794 | 147 |
| | | 5000K | 4777 | 143 |
| 7,500 | 52 | 3000K | 7169 | 133 |
| | | 4000K | 7403 | 144 |
| | | 5000K | 7291 | 137 |
| 10,000 | 75 | 3000K | 9504 | 123 |
| | | 4000K | 9894 | 136 |
| | | 5000K | 9529 | 125 |



Specifications

INTENDED USE:

The CNY LED ALO canopy luminaire is ideal for surface mount application such as canopies over building entrances, walkways, loading docks, and covered parking areas. The products traditional style does not detract from current building aesthetics, creating a seamless upgrade. These products are energy-efficient replacements of existing surface mount products; up to 250W metal halide.

CNY LED ALO features adjustable lumen output include low, medium, and high. Switchable CCT includes 3000K (warm), 4000K (neutral), or 5000K (daylight), a selectable integral photocell that automatically turns the fixture on in the evening and off the next morning, and a selectable integral occupancy sensor that can turn on the fixture when motion is detected and be set to maintain 10% illumination or fully off when no motion is detected.

CONSTRUCTION:

The CNY LED ALO has a cast-aluminum housing with powder coat finish for lasting durability. The IK08 impact rated frosted lens is designed for uniform light distribution while providing visually comfortable illumination. The lens is sealed with a one piece gasket creating an IP65 rated fixture. Rated for temps -25C to 25C.

ELECTRICAL:

Standard 6kV surge protection tested in accordance to ANSI/IEEE C62.41.2 Category C. CNY LED ALO luminaires use UVOLT (120-347V). Adjustable lumen output is achieved with 0-10V continuous dimming capable drivers, ensuring system power factor > 90% and THD < 20%. High-efficiency LEDs maintains over 70% of light output at 100,000 hours (L70 > 100,000 hours).

INSTALLATION:

The CNY LED ALO canopy luminaire features a quick-mount plate that makes mounting to a recessed junction box or conduit entry point both quick and trouble free. The quick-mount plate can be separated for surface mounting and reattached via a hinge for support while wiring. Four 3/4" NPT conduit entry points are built into the quick-mount plate to allow fast and confident alignment for surface-conduit wiring.

LISTINGS:

UL Listed to U.S. and Canadian safety standards for wet locations. Tested in accordance with IESNA LM-79 and LM-80 standards.

DesignLights Consortium® (DLC) Premium qualified product. Not all versions of this product may be DLC Premium qualified. Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which versions are qualified.

Can be used to comply with California Title 24, Part 6 High Efficacy LED Light Source Requirements

WARRANTY:

5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at: www.acuitybrands.com/support/warranty/terms-and-conditions

Note: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

Dimensions

CNY LED ALO





Width: 10" (25.4cm)

Height: 3" (7.62cm)

Depth: 10" (25.4cm)

Weight: 4.8lbs (2.18kg)

All dimensions are inches (centimeters) unless otherwise indicated.



Location of Side Conduit KO Holes

Occupancy Sensor Settings

10% Dim




Toggled On



Toggled Off



Time to Off with No Occupancy is 10 minutes



Factory Settings

| | |
|------------------|--------|
| Lumen Output | 10,000 |
| CCT | 4000K |
| Photocell | Off |
| Occupancy Sensor | Off |