


PROJECT NAME:

QUANTITY:

TYPE:

ORDERING CODE:



- ① Ø 5.2" (132mm) ceiling mount canopy.
- ② Field adjustable suspension stem or silver braided power cable with aircraft safety cable. Also, offered with a catenary suspension attachment.
- ③ Ø 3" (76mm) seamless extruded aluminum housing for electrical components.
- ④ Ø 3" (76mm) white translucent high impact UV stabilized acrylic lens.



CL312/CL322/CL342

MATERIALS

Lumistik pendant is made of corrosion resistant 356 aluminum alloy with a copper (CU) content of less than 0.1%. LED is contained in a white UV stabilized high impact acrylic sealed cylinder. The assembly is designed to provide a uniform column illumination. Lumistik pendant is available with three standard acrylic lengths.

ELECTRICAL DRIVER

Driver is 0-10V dimming-ready (dims to 10%) with: 120-277 multi-volt compatibility (50-60Hz), operating temperatures of -40°C to +55°C/-40°F to +131°F, output over voltage protection, output over current protection, output short circuit protection with auto-recovery. Driver for RGBW operating temperature range -40°C to +50°C/-4°F to +122°F

LED LIGHT ENGINE

Offered in 2700K/3000K/3500K/4000K CCT with 80 CRI. Optional RGBW. 60,000hrs L70B50 (based on IESNA TM-21 Test Method and LM-80 data).

FINISH

Five-stage preparation process includes preheating of cast aluminum parts for air extraction. Polyester powder coating is applied through an electrostatic process, and oven cured for long term finish.

CERTIFICATION

UL Certified to Canadian and U.S. safety standards. Certified for use in wet locations. Rated IP65. The ceiling canopy is damp location only. Photometric testing performed by an independent laboratory in accordance with IES LM-79-08 standards at 25°C. Actual performance may differ as a result of end-user environment and application.

WARRANTY


5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at: <https://www.acuitybrands.com/support/warranty/terms-and-conditions>

MOUNTING


Mounts on a standard 4" (102mm) octagonal electrical box with 3.5" (89mm) C/C mounting holes. Fixture must be installed on a finished ceiling for exterior applications and/or when exposed to inclement weather.

MEASUREMENTS

Maximum weight: CL312: 4 lbs (1.9 kg)
CL322: 5 lbs (2.3 kg)
CL342: 7 lbs (3 kg)



ORDERING CODE

*SERIES	*LIGHT OUTPUT	*CCT	*VOLTAGE	*MOUNTING	*LENGTH
<div>CL312</div> 	<u>Static White</u>	27K 2700K	120 120V	CAT3 Catenary suspension attachment	12IN 12"
	L4L10 830 lm/9w	30K 3000K	277 277V	SPG Silver braided power cord with aircraft cable ³	24IN 24"
	<u>RGBW</u>	35K 3500K	MVOLT 120V-277V		36IN 36"
	L4RGBW 662 lm/12w ^{1,2}	40K 4000K		48IN 48"	
		RGBW RGB + white 4000K		60IN 60"	
Delivered lumens calculated at 4000K/80CRI except for RGBW. Typical power consumption. Refer to LCF table for outputs at other CCTs. For RGBW, values are for total delivered lumens. 662 lm/ft. For individual maximum output values, refer to RGBW details section.					Available up to 240" in 12" increments. Required field for SPG, STM

FUSE	SURGE PROTECTOR	EMERGENCY	*FINISH	ENVIRONMENT
FS Fuse	SP Surge protector	REM7 Remote emergency battery, 90 min, 7W ⁴	BKT Jet black BZT Bronze CHT Champagne DGT Gun metal GRT Titanium gray MST Matte silver SGT Steel gray WHT Snow white CMC Custom matched color ⁵ RAL RAL color ⁶	MG Marine grade paint ⁷

NOTES

*- Denotes a required field

1- Not available with REM7 or STM. OAH increases, see RGBW dimensions for details.

2- Available only with RGBW option.

3- Not suitable for outdoor locations.

4- Remote mount 50ft - 12" square enclosure with access cover. The remote enclosure must be interior. Cable between fixture and remote box is provided by other.

5- Contact factory to coordinate custom matching color.

6- Specify RAL number.

7- Marine grade paint for harsh, coastal environment and exposure to salt water. Additional delay required.

LUMINIS.COM


Toll free: (866) 586-4647 | Fax: (514) 683-8872 | Email: info@luminis.com

260 Labrosse, Pointe-Claire (QC) Canada H9R 5L5

CL312/CL322/CL342

Rev. 11/19/24

ORDERING CODE

*SERIES	*LIGHT OUTPUT	*CCT	*VOLTAGE	*MOUNTING	*LENGTH
<div>CL322</div> 	<u>Static White</u>	27K 2700K	120 120V	CAT3 Catenary suspension attachment	12IN 12"
	L4L10 830 lm/9w	30K 3000K	277 277V	SPG Silver braided power cord with aircraft cable ³	24IN 24"
	L4L15 1640 lm/16w	35K 3500K	MVOLT 120V-277V		36IN 36"
	L4L20 2250 lm/21w	40K 4000K		48IN 48"	
	<u>RGBW</u>	RGBW RGB + white 4000K		STM Field-cutable hang straight stem	60IN 60"
	L4RGBW 1325 lm/24w ^{1,2}		Available up to 240" in 12" increments. Required field for SPG, STM		
	Delivered lumens calculated at 4000K/80CRI except for RGBW. Typical power consumption. Refer to LCF table for outputs at other CCTs. For RGBW, values are for total delivered lumens. 662 lm/ft. For individual maximum output values, refer to RGBW details section				

FUSE	SURGE PROTECTOR	EMERGENCY	*FINISH	ENVIRONMENT
FS Fuse	SP Surge protector	REM7 Remote emergency battery, 90 min, 7W ⁴	BKT Jet black BZT Bronze CHT Champagne DGT Gun metal GRT Titanium gray MST Matte silver SGT Steel gray WHT Snow white CMC Custom matched color ⁵ RAL RAL color ⁶	MG Marine grade paint ⁷

NOTES

*- Denotes a required field

1- Not available with REM7 or STM. OAH increases, see RGBW dimensions for details.

2- Available only with RGBW option.

3- Not suitable for outdoor locations.

4- Remote mount 50ft - 12" square enclosure with access cover. The remote enclosure must be interior. Cable between fixture and remote box is provided by other.

5- Contact factory to coordinate custom matching color.


6- Specify RAL number.

7- Marine grade paint for harsh, coastal environment and exposure to salt water. Additional delay required.

LUMINIS.COM

Toll free: (866) 586-4647 | Fax: (514) 683-8872 | Email: info@luminis.com
 260 Labrosse, Pointe-Claire (QC) Canada H9R 5L5

ORDERING CODE

*SERIES	*LIGHT OUTPUT	*CCT	*VOLTAGE	*MOUNTING	*LENGTH
<div>CL342</div> 	<u>Static White</u>	27K 2700K	120 120V	CAT3 Catenary suspension attachment	12IN 12"
	L8L20 1900 lm/16w	30K 3000K	277 277V	SPG Silver braided power cord with aircraft cable ³	24IN 24"
	L8L40 3850 lm/30w	35K 3500K	MVOLT 120V-277V		36IN 36"
	<u>RGBW</u>	40K 4000K	STM Field-cuttable hang straight stem	48IN 48"	
	L8RGBW 2650 lm/48w ^{1,2}	RGBW RGB + white 4000K		60IN 60"	
Available up to 240" in 12" increments. Required field for SPG, STM					
Delivered lumens calculated at 4000K/80CRI except for RGBW. Typical power consumption. Refer to LCF table for outputs at other CCTs. For RGBW, values are for total delivered lumens. 662 lm/ft. For individual maximum output values, refer to RGBW details section.					

FUSE	SURGE PROTECTOR	EMERGENCY	*FINISH	ENVIRONMENT
FS Fuse	SP Surge protector	REM7 Remote emergency battery, 90 min, 7W ⁴	BKT Jet black BZT Bronze CHT Champagne DGT Gun metal GRT Titanium gray MST Matte silver SGT Steel gray WHT Snow white CMC Custom matched color ⁵ RAL RAL color ⁴	MG Marine grade paint ⁷

NOTES

*- Denotes a required field

1- Not available with REM7 or STM. OAH increases, see RGBW dimensions for details.

2- Available only with RGBW option.

3- Not suitable for outdoor locations.

4- Remote mount 50ft - 12" square enclosure with access cover. The remote enclosure must be interior. Cable between fixture and remote box is provided by other.

5- Contact factory to coordinate custom matching color.

6- Specify RAL number.

7- Marine grade paint for harsh, coastal environment and exposure to salt water. Additional delay required.

LUMINIS.COM

Toll free: (866) 586-4647 | Fax: (514) 683-8872 | Email: info@luminis.com


260 Labrosse, Pointe-Claire (QC) Canada H9R 5L5

CL312/CL322/CL342

Rev. 11/19/24


TYPICAL PHOTOMETRY SUMMARY

CL312-L4L10




Total Lms: 830 Lumens
Total Input Watts: 9 W
Efficacy: 92 Lumens/Watt
BUG: B0-U3-G1
CCT/CRI: 4000K/80
Maximum Candela: 84 @ 0°/98°V

CL322-L4L20



Total Lms: 2250 Lumens
Total Input Watts: 21 W
Efficacy: 107 Lumens/Watt
BUG: B1-U4-G2
CCT/CRI: 4000K/80
Maximum Candela: 228 @ 0°/95°V

CL342-L8L40



Total Lms: 3850 Lumens
Total Input Watts: 30 W
Efficacy: 129 Lumens/Watt
BUG: B1-U5-G2
CCT/CRI: 4000K/80
Maximum Candela: 391 @ 0°/92°V

LUMEN CONVERSION FACTOR (LCF)

CCT	CRI	LCF
2700K	80	0.91
3000K	80	0.94
3500K	80	0.98
4000K	80	1.00

All Photometry shown use the 80CRI 4000K LEDs.
Please visit our web site www.luminis.com for complete I.E.S. file.

LUMINIS.COM

Toll free: (866) 586-4647 | Fax: (514) 683-8872 | Email: info@luminis.com
260 Labrosse, Pointe-Claire (QC) Canada H9R 5L5


© 2024 Acuity Brands Lighting Canada, Inc. All rights reserved. Specifications subject to change without notice.

CL312/CL322/CL342

Rev. 11/19/24

Page 5 of 7

OPTION DETAILS



CAT3

Cast aluminum catenary junction box with 4 sealed connectors by Luminis and pre-inserted into housing. Ready to accept 1/4" or 1/2" stainless steel suspension cable. (Structural design, power cable, control cable, stainless steel catenary cable, cable fittings, and fittings for mounting to support structure provided by others.)

