


PROJECT NAME:

QUANTITY:

TYPE:

ORDERING CODE:



- ① Ø 5" (127mm) canopy with universal mounting plate.
- ② Field adjustable suspension stem or silver braided power cable with aircraft safety cable. Also, offered with a catenary suspension attachment.
- ③ Extruded aluminum driver housing.
- ④ LED heat sink.
- ⑤ Aluminum extruded reflector housing.



AR70

## MATERIALS

Aramis is made of an extruded aluminum housing designed to optimize functionality of the driver and solid state components. Cast aluminum heat sink to optimize heat management and luminaire efficacy. LED array is mechanically secured and easily removable for maintenance or upgrade. Aluminum faceted reflector designed to optimize the LED light source performance and uniformity.

## ELECTRICAL DRIVER

120V/277V driver is 0-10V dimming-ready (min. dim to 5%) with 120-277 multi-volt compatibility (50-60Hz), operating temperature range of -20°C/-4°F to +50°C/122°F, output over voltage protection, output over current protection and output short circuit protection with auto-recovery.

347V driver is 0-10V dimming ready (min. dim to 1%)\* with operating temperature range of -20°C/-4°F to +50°C/122°F, over current and output short circuit protection.

## LED LIGHT ENGINE

Offered in 2700K, 3000K, 3500K & 4000K / 80CRI.  
70% LED lumen maintenance at 125,000 hours (L70/B50) based on IESNA LM-80-08 LED extrapolated life, calculated per IESNA TM-21-21.

## FINISH

Five-stage preparation process includes preheating of cast aluminum parts for air extraction. Polyester powder coating is applied through an electrostatic process, and oven cured for long term finish.

## CERTIFICATION

UL Certified to Canadian and U.S. safety standards. Certified for use in damp location. Rated IP20. Photometric testing performed by an independent laboratory in accordance with IES LM-79-08 standards at 25°C. Actual performance may differ as a result of end-user environment and application.

\* L1L65 light output dims to min. 1%, L1L85, L1L100 dims to min. 5%, L1L120, L1L160, L1L180 dims to min. 10%

## WARRANTY


5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at: <https://www.acuitybrands.com/support/warranty/terms-and-conditions>

## MOUNTING

Mounts on a standard 4" (102mm) octagonal electrical box with 3.5" (89mm) C/C mounting holes.

## MEASUREMENTS

Maximum weight: 12.2 lbs (5.5 kg)




## LUMINIS.COM

Toll free: (866) 586-4647 | Fax: (514) 683-8872 | Email: [info@luminis.com](mailto:info@luminis.com)  
260 Labrosse, Pointe-Claire (QC) Canada H9R 5L5

© 2025 Acuity Brands Lighting Canada, Inc. All rights reserved. Specifications subject to change without notice.

## ORDERING CODE

*SERIES	*LIGHT OUTPUT	DISTRIBUTION	*CCT	*VOLTAGE	CONTROLS
	<b>L1L65</b> 6511 lm / 54w	<b>WD</b> Wide optic 55°	<b>27K</b> 2700K	<b>120</b> 120V	<b>NLTAIR2</b> nLight AIR 2.0 <sup>2</sup>
	<b>L1L85</b> 8635 lm / 76w		<b>30K</b> 3000K	<b>277</b> 277V	
	<b>L1L100</b> 10029 lm / 84w	<b>VWD</b> Very wide optic 80°	<b>35K</b> 3500K	<b>347</b> 347V	
	<b>L1L120</b> 12003 lm / 105w		<b>40K</b> 4000K	<b>MVOLT</b> 120V-277V	
	<b>L1L160</b> 15733 lm / 140w <sup>1</sup>				
	<b>L1L180</b> 18168 lm / 170w <sup>1</sup>				
Delivered lumens calculated at 4000K/80CRI. Typical power consumption. Refer to LCF table for outputs at other CCTs.					

*MOUNTING	SUSPENSION LENGTH	FUSE	EMERGENCY	*FINISH
<b>CAT3</b> Catenary suspension attachment	<b>12IN</b> 12"	<b>FS</b> Fuse	<b>REM7</b> Remote emergency battery, 90 min, 7W <sup>3</sup>	<b>BKT</b> Jet black
<b>HK</b> Male hook with 0.43" opening Includes 36" 5/18 black power cord. Hook height 3.5"	<b>24IN</b> 24"			<b>BZT</b> Bronze
	<b>36IN</b> 36"			<b>CHT</b> Champagne
<b>SPG</b> Silver braided suspension power cord with aircraft cable	<b>48IN</b> 48"			<b>DGT</b> Gun metal
	<b>60IN</b> 60"			<b>GRT</b> Titanium gray
<b>STM</b> Field-cuttable hang straight suspension stem				<b>MST</b> Matte silver
<b>TA</b> 3/4" NPT conduit adaptor				<b>SGT</b> Steel gray
				<b>WHT</b> Snow white
				<b>CMC</b> Custom matched color <sup>4</sup>
				<b>RAL</b> RAL color <sup>5</sup>


Available up to 240" in 12" increments. Required field for SPG, STM.	
--	--

### NOTES

- \*- Denotes a required field
- 1- Overall height of fixture is 23.5" (597mm) for this model.
- 2- 120V, 277V or MVOLT only. Installed in Ø15" canopy with STM/SPG. Refer to the mounting image for more details. Not available for L1L120, L1L160, L1L180, REM7, CAT3, TA, HK.
- 3- Remote mount 50ft - 12" (305mm) square enclosure with access cover. Not available with 347V or CAT3. The remote enclosure must be interior. Cable between fixture and remote box is provided by others.
- 4- Contact factory to coordinate custom matching color.
- 5- Specify RAL number.


## TYPICAL PHOTOMETRY SUMMARY

AR70-L1L180



**Total Lms:** 18,168 Lumens  
**Total Input Watts:** 170 W  
**S/MH** = 0.82  
**CCT/CRI:** 4000K/80  
**Maximum Candela:** 23,418 @  
 0°/0°V

AR70-L1L180-VWD



**Total Lms:** 19,210 Lumens  
**Total Input Watts:** 170 W  
**S/MH** = 0.82  
**CCT/CRI:** 4000K/80  
**Maximum Candela:** 7,996 @  
 0°/40°V

### LUMEN CONVERSION FACTOR (LCF)

CCT	CRI	LCF
2700K	80	0.92
3000K	80	0.95
3500K	80	0.98
4000K	80	1.00


All Photometry shown use the 80CRI 4000K LEDs.  
 Please visit our web site [www.luminis.com](http://www.luminis.com) for complete I.E.S. file.

## LUMINIS.COM


Toll free: (866) 586-4647 | Fax: (514) 683-8872 | Email: [info@luminis.com](mailto:info@luminis.com)  
 260 Labrosse, Pointe-Claire (QC) Canada H9R 5L5


© 2025 Acuity Brands Lighting Canada, Inc. All rights reserved. Specifications subject to change without notice.


## OPTION DETAILS



CANOPY TOP VIEW



**NLTAIR2 (STM & SPG)**   
Ø11" canopy with nLight AIR  
Control gen2 and black antenna.  
For the following light outputs:  
L1L65, L1L85, L1L100




**REM7**  
7W Remote mount 120/277V  
emergency battery pack.




**SPG**  
Silver braided power cord with  
onsite adjustable aircraft safety  
cable.



**STM**  
Heavy duty 45° hang straight  
swivel, with Ø 5" (127mm) canopy  
and universal mounting plate with  
Ø 7/8" (22mm) suspension stem  
with aircraft safety cable.



### ANGLE ADJUSTMENT MECHANISM



**Power cable in:**  
3 conductor x 14  
gauge AWG. The  
2 cable glands  
located at the top  
can accommodate a  
cable ranging from  
10mm - 14mm.

**Control cable in:**  
The 2 cable glands  
on the bottom can  
accommodate a  
cable ranging from  
6mm - 11mm.

### CAT3

Cast aluminum catenary junction box with 4 sealed connectors by Luminis and pre-inserted into housing. Ready to accept 1/4" or 1/2" stainless steel suspension cable.  
Weight: 15.5 lbs (7 kg)  
(Structural design, power cable, control cable, stainless steel catenary cable, cable fittings, and fittings for mounting to support structure provided by others.)