

Catalog Number
Notes
Type

FEATURES & SPECIFICATIONS

INTENDED USE — SBL4W LED wraparound provides a digital lighting platform to deliver general ambient lighting for surface-mount applications. The SBL4W provides a similar look to that of an existing fluorescent wrap with all of the excellent benefits of LED: energy savings, long life, and maintenance savings. Ideal for closets, storage rooms, and offices.

CONSTRUCTION — Linear side prisms control brightness, pyramidal bottom prisms minimize lamp image. Continuous side flanges on fixture body provide light trap and continuous diffuser support to prevent accidental opening and simplify maintenance. Full depth, white enamel end plates.

Die-formed from code gauge cold-rolled steel. Channel cover snaps into place without the use of tools. Full end cap factory installed to reduce job site labor.

OPTICS — The translucent white diffuser reduces glare and pixilation without impacting performance.

ELECTRICAL — Long-life LEDs, coupled with high-efficiency drivers, provide superior quantity and quality of illumination for extended service life. 90% LED lumen maintenance at 50,000 hours (L90/50,000). The LEDs have a CRI of 82.

LISTINGS — CSA certified to meet U.S. and Canadian standards.

Damp listed.

WARRANTY — 5-year limited warranty. Complete warranty terms located at:

www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx

Note: Actual performance may differ as a result of end-user environment and application.

All values are design or typical values, measured under laboratory conditions at 25 °C.

Specifications subject to change without notice.

Square-basket LED Wraparound

SBL4W



4' Length
Wide Housing'
LED

Specifications:

Length: 48 (121.9)

Width: 14 3/16 (36.0)

Height: 2 3/4 (7.0)

All dimensions are inches (centimeters) unless otherwise indicated.

ORDERING INFORMATION Lead times will vary depending on options selected. Consult with your sales representative. **Example:** SBL4W 6500LM 80CRI 40K MIN1 GZT MVOLT

SBL4W		Lumens		CRI		Color temperature		Minimum Dimming Level		Control		Voltage	
Series													
SBL4W	4' LED wrap	6500LM	6500 lumens	80CRI	80 CRI	40K	4000 K	MIN1	Dims to 1%	GZT	Generic 0-10V Dimming	MVOLT	120-277V

Performance Data			
Lumen Package	Lumens	Input Watts	LPW
6500LM 80CRI 40K	6564	52.7	125