

## FEATURES & SPECIFICATIONS

### INTENDED USE

Provides general illumination in residential applications. Ideal for use in closets, foyers, hallways, corridors, bedrooms, offices, utility work areas, stairways and more. **If required for commercial applications or operation more than eight (8) hours per day, select a commercial-rated flush mount.**

### CONSTRUCTION

Features a white acrylic diffuser with a defined outer edge. Diffuser twist-locks into housing for a hardware-free appearance and provides easy access for cleaning.

### OPTICS

Produces 2040 lumens at 50,000 hours life. LEDs rated for 50,000 hours of use, LED driver rated for 30,000 hours of use.

### ELECTRICAL

Fixture operates at 120 volts, 60 Hz. Standard input = 30 watts, 68 lumens per watt.

Works with most standard incandescent dimmers (see list of approved dimmers).

### INSTALLATION

All mounting hardware included.

### LISTINGS

UL Certified to US and Canadian standards and listed suitable for damp locations.

### WARRANTY

5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at:

[www.acuitybrands.com/support/warranty/terms-and-conditions](http://www.acuitybrands.com/support/warranty/terms-and-conditions)

**NOTE:** Actual performance may differ as a result of end-user environment and application.

All values are design or typical values, measured under laboratory conditions at 25°C.

Specifications subject to change without notice.

Catalog Number
Notes
Type

Decorative Indoor

# Hildon Residential LED Flush Mount

HIGH-PERFORMANCE LED



### Specifications

Height: 3-3/16 (8.1)

Diameter: 14 (35.6)

Weight: 2.1 lbs

All dimensions are inches (centimeters) unless otherwise indicated.

### ORDERING INFORMATION

For shortest lead times, configure product using **bolded options**.

**Example:** FMHLDL 14 20840

Series	Module/CRI	Color temperature
<b>FMHLDL 14</b> 14 Hildon LED flush mount, 14"	<b>208</b> >80CRI	<b>40</b> 4000 K <b>30</b> 3000 K <sup>1</sup>

# LED Hildon Flush Mount

## LIGHTING FACTS

