



Catalog Number
Notes
Type

Contractor Select™

L7X

6" Incandescent Line Voltage Housing and Trim

Approved for direct burial in insulation and all ceiling and wiring types, these air-tight 6" recessed incandescent housings are rated IC/Non-IC for 2x8 new construction applications. New construction housings feature factory-installed captive bar hangers that span up to 24 o.c. and feature a stepped shank nail with integral T-bar locks. Two locking screws hold the fixture position. The socket clips to trim to ensure proper and consistent lamp position.

FEATURES:

- Damp location listed
- Retaining clips riveted to top of reflector hold trim inside housing
- Suitable for ceilings up to 1-1/2" thick
- Trim options include 6" Open and Baffle
- All trims are available in a white finish



CO1



Catalog Number	UPC	Description	Lamp Source	Voltage	Socket	Pallet qty.
L7X R6	784231091906	6" New Construction Housing	Incandescent	120V	E26 Screw Shell	120

Trims

Catalog Number	UPC	Description	Flange Range	Finish	Lamp Included	Pallet qty.
CO1 R6	745973753095	6" Open Trim	Wide	White	No	450

Accessories: Order as separate catalog number.

HS6875	6-7/8" hole saw
CTR6	6" goof ring, white (8-3/4" O.D.)



Specifications

L7X

INTENDED USE:

Recessed housing rated IC or Non-IC. For new construction only. Approved for all ceiling and wiring types. Approved for direct burial in insulation.

INSTALLATION:

Air-Tight housing suitable for air-tight installations. 2 x 8 wood joist or T-bar installation. Expandable bar hangers allow for off center mounting in wood joist or T-bar ceilings. Length of 25 1/4" maximum 13 1/4" minimum or cut to fit 9" on center joist construction. Vertical adjustment of housing allows for flush mounting with ceiling face. Suitable to ceilings up to 1-1/2" thick.

LISTINGS:

UL Listed to US and Canadian safety standards. Damp location listing. (See trim selection for wet location listing).

WARRANTY:

1-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at:

www.acuitybrands.com/support/warranty/terms-and-conditions

Note: Actual performance may differ as a result of end-user environment and application. Specifications subject to change without notice.

Dimensions

All dimensions are inches (centimeters) unless otherwise indicated.

Height: 6-7/8 (17.5)

Length: 15 (38.1)

Width: 13-7/8 (35.2)

Ceiling cutout: 7 (17.8)



Specifications

CO1

INTENDED USE:

For use with housings L7X, L7XR.

INSTALLATION:

Socket to trim interface. Retaining clips riveted to top of reflector hold trim inside housing.

LISTINGS:

UL Listed to US and Canadian safety standards. Damp location listing.

WARRANTY:

1-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at:

www.acuitybrands.com/support/warranty/terms-and-conditions

Note: Actual performance may differ as a result of end-user environment and application. Specifications subject to change without notice.

Dimensions

All dimensions are inches (centimeters) unless otherwise indicated.

Height: 5-7/8 (14.9)

Lamp opening: 4-1/4 (10.8)

Diameter: 7-3/4 (19.7)