



Catalog Number
Notes
Type

Contractor Select™

WF4/WF6

4" & 6" LED Switchable White Color Temperature

The 4" and 6" Wafer™ LED Downlight with Switchable White provides high-quality light output and efficiency featuring a switch for easy color temperature adjustment - while eliminating the need for recessed housings. The innovative, slim design allows for easy retrofit, remodel or new construction installation from below the ceiling. The Wafer LED downlight is wet location listed - making it ideal for use in a breadth of outdoor residential, hospitality, commercial and multifamily applications.

FEATURES:

- Edge-lit LED technology uses light guided plate to distribute light. Polycarbonate lens provides even illumination throughout the space.
- Two remote selectable color temperature options, each with a setting choice to choose either 2700K, 3000K, and 3500K or 3000K, 4000K, and 5000K using the switch.
- Minimum 90 CRI



Catalog Number	UPC	Description	Replaces up to	Lumens	Input Watts	CCT	CRI	Voltage	Finish	Pallet qty.
WF4 LED 27K30K35K 90CRI MW M6	191848253403	4" Wafer-Thin LED Downlight	65W Incandescent	730/800/780	10.5W	2700K/3000K/3500K	90	120V	White	576
WF4 LED 30K40K50K 90CRI MW M6	191848253557	4" Wafer-Thin LED Downlight	65W Incandescent	750/810/790	10.5W	3000K/4000K/5000K	90	120V	White	432
WF6 LED 27K30K35K 90CRI MW M6	191848253861	6" Wafer-Thin LED Downlight	75W Incandescent	1040/1150/1110	14W	2700K/3000K/3500K	90	120V	White	450
WF6 LED 30K40K50K 90CRI MW M6	191848253946	6" Wafer-Thin LED Downlight	75W Incandescent	1090/1190/1120	14W	3000K/4000K/5000K	90	120V	White	450

Accessories: Order as separate catalog number.

WF4 PAN R12	4" new construction pan, retail pack of 12
WF6 PAN R12	6" new construction pan, retail pack of 12
WF8643 Pan U	Universal new construction pan
WFJB U	Remodel joist bar
WFEXC6 SW3PIN FT4	3-Pin 6ft Cable
WFEXC10 SW3PIN FT4	3-Pin 10ft Cable
WFEXC20 SW3PIN FT4	3-Pin 20ft Cable
WF4GR MW JZ	4" Wafer Goof Ring 4.2" ID x 6.2" OD
WF6GR MW JZ	6" Wafer Goof Ring 6" ID x 8" OD

* Goof rings are made of 22 gauge steel and painted white.



Specifications

INTENDED USE:

The 4" and 6" Wafer™ LED Downlight with Switchable White provides high-quality light output and efficiency featuring a switch for easy color temperature adjustment - while eliminating the need for recessed housings. The innovative, slim design allows for easy retrofit, remodel or new construction installation from below the ceiling. The Wafer LED downlight is wet location listed - making it ideal for use in a breadth of outdoor residential, hospitality, commercial and multifamily applications.

CONSTRUCTION:

Aluminum die cast outer frame. Durable, powder coat paint to prevent rust. FT4 plenum rated cable connector to connect from module to remote driver box. IC rated driver with convenience and value of two remote selectable color temperature options, each with a setting choice to choose either 2700K, 3000K, and 3500K or 3000K, 4000K, and 5000K using the switch. The isolated driver integrated inside steel remote box with four 7/8" knockouts with slots for pryout. Suitable for pulling wires with the 12 cubic-inch wiring compartment to accommodate up to (6) 14 gauge insulated conductor or (4) 12 gauge insulated conductors, making the Wafer LED Downlights much easier to wire in 2in/2out (plus ground) daisy-chain applications and contractor friendly.

ELECTRICAL:

Connect directly to 120V power supply via provided UL recognized driver. High efficient driver with power factor > 0.9. Ambient operating temperature: -40°F (-40°C) to +104°F (+40°C). Dimming down to 10% with most standard incandescent dimmers (see list of approved dimmers). Replaces 65W incandescent for 750 lumens (WF4) and 100W incandescent for 1150 lumens (WF6).

INSTALLATION:

Ideal for shallow ceiling plenum; no housing required. Steel spring clip for easy installation. 4" or 6" cut out template is provided to ensure a correct sized hole is cut into ceiling for proper installation of the trim. Size of hole should not exceed 4 1/4 inches for the WF4 and 6 1/6 inches for the WF6. Suitable for installation in t-grid and drop ceiling applications. 2" plenum space required for installation of the remote driver box.

LISTINGS:

CSA certified to US and Canadian safety standards. ENERGY STAR® certified. Suitable for wet location, covered ceiling. Air Tight certified in accordance with ASTM E283-2004. NOM Certified. Can be used to comply with California Title 24 Part 6 High Efficacy LED Light Source Requirements.

WARRANTY:

5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at:

www.acuitybrands.com/support/warranty/terms-and-conditions

Note: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

Dimensions

WF4

Aperture: 3.2 (8.1)
Ceiling opening: 4.2 (10.7)
Overlap trim: 4.7 (12.0)
Height: 1.1 (2.8)

WF6

Aperture: 4.9 (12.4)
Ceiling opening: 6 (15.2)
Overlap trim: 6.7 (17)
Height: 1.1 (2.8)

All dimensions are inches (centimeters) unless otherwise indicated.

