



Juno® Trac-Lites™ System

A complete and customizable track system with an array of features

Juno®

Juno[®] Trac-Lites[™] System



Track sections are constructed of extruded aluminum and offer a low 1/2" profile that unobtrusively hugs the ceiling. Attractive yet affordable, they incorporate all the popular Juno Trac features, including debossed polarity indicators for fast, sure alignment. Standard track sections are available in 2', 4', 6' and 8' lengths with 12-gauge copper conductors. They can be easily cut to custom lengths in the field. A comprehensive selection of electrical feeds and connectors completes this highly versatile system.

Track Sections & Electrical Feeds


Track Sections



Features

- Low 1/2" profile fits snugly to ceiling
- Rigid extruded aluminum channel
- Standard solid 12-gauge copper conductors
- 20 Amp capacity
- Debossed polarity line provides visual alignment with fixture and connector polarity arrows
- One circuit only
- Dead end and mounting hardware included
- Can be cut to custom length by installer

Catalog #	Finish	Description
R 2FT WH	White	2' One-Circuit Track (19-7/8" actual length)
R 2FT BL	Black	
R 2FT SL	Silver	
R 2FT BZ	Bronze	
R 4FT WH	White	4' One-Circuit Track (43-7/8" actual length)
R 4FT BL	Black	
R 4FT SL	Silver	
R 4FT BZ	Bronze	
R 6FT WH	White	6' One-Circuit Track (67-7/8" actual length)
R 6FT BL	Black	
R 6FT SL	Silver	
R 6FT BZ	Bronze	
R 8FT WH	White	8' One-Circuit Track (91-7/8" actual length)
R 8FT BL	Black	
R 8FT SL	Silver	
R 8FT BZ	Bronze	



Track Dead End



Track Dead Feed

Catalog #	Finish	Description
R28 WH	White	<ul style="list-style-type: none"> • Only required when terminating extra field cut-off sections • One supplied with track section
R28 BL	Black	
R28 SL	Silver	
R28 BZ	Bronze	




Electrical Feeds




End Feed Connector and Outlet Box Cover

Catalog #	Finish	Description
R21 WH	White	<ul style="list-style-type: none"> • For outlet box feed • Includes outlet box cover, fixture strap, and ground screw
R21 BL	Black	
R21 SL	Silver	
R21 BZ	Bronze	











End Feed Connector

Catalog #	Finish	Description
R38 WH	White	<ul style="list-style-type: none"> • Feeds track from above with Flex or BX • Accepts standard 1/2" electrical connector
R38 BL	Black	
R38 SL	Silver	
R38 BZ	Bronze	
R38 RP WH	White	<ul style="list-style-type: none"> • Same as above except designed for use in opposite polarity orientation compared to standard feed connectors • See specification sheets for more details
R38 RP BL	Black	



Electrical Feeds













Electrical Feeds (cont)

 <p>Conduit Feed</p>	<p>Catalog # R34 WH R34 BL R34 SL R34 BZ</p>	<p>Finish White Black Silver Bronze</p>	<p>Description</p> <ul style="list-style-type: none"> For surface wiring using standard 1/2" electrical connector <hr/> <ul style="list-style-type: none"> Same as above except designed for use in opposite polarity orientation compared to standard feeds See specification sheets for more details 	<p>Dimensions</p> 
 <p>T-Bar End Feed</p>	<p>Catalog # R36 WH R36 BL R36 SL R36 BZ</p>	<p>Finish White Black Silver Bronze</p>	<p>Description</p> <ul style="list-style-type: none"> Wiring compartment contains standard 1/2" K.O.'s Feeds track from above when 15/16" T-bar is directly above track <hr/> <ul style="list-style-type: none"> Same as above except designed for use in opposite polarity orientation compared to standard feeds See specification sheets for more details 	<p>Dimensions</p> 
 <p>Floating Electrical Feed</p>	<p>Catalog # R29 WH R29 BL R29 SL R29 BZ</p>	<p>Finish White Black Silver Bronze</p>	<p>Description</p> <ul style="list-style-type: none"> Permits mounting at any point along track at outlet box Includes floating connector, outlet box cover, and track dead end 	<p>Dimensions</p> 
 <p>Cord and Plug Connector</p>	<p>Catalog # R22 WH R22 BL R22 SL R22 BZ</p>	<p>Finish White Black Silver Bronze</p>	<p>Description</p> <ul style="list-style-type: none"> 15' 2-wire white cord Includes surface wire retainers and in-line switch 7 Amp maximum Not UL Rated <hr/> <ul style="list-style-type: none"> Same as above but with three wires and matching color cords No switch 7 Amp maximum Not UL Rated 	<p>Dimensions</p> 

The product and system may be covered by the following United States patent: US 5,259,774

Connectors




Connectors




 <p>Miniature Straight Connector</p>	<p>Catalog # Finish Description</p> <p>R23 WH White R23 BL Black R23 SL Silver R23 BZ Bronze</p>	<p>Description</p> <ul style="list-style-type: none"> Joins two track sections end to end 	<p>Dimensions</p> 
 <p>Flexible Adjustable Joiner</p>	<p>Catalog # Finish Description</p> <p>R20 WH White R20 BL Black R20 SL Silver R20 BZ Bronze</p>	<p>Description</p> <ul style="list-style-type: none"> Joins two track sections Can flex to 90° to the left, right, up or down 	<p>Dimensions</p> 
 <p>Adjustable Connector</p>	<p>Catalog # Finish Description</p> <p>R24 WH White R24 BL Black R24 SL Silver R24 BZ Bronze</p>	<p>Description</p> <ul style="list-style-type: none"> Joins two track sections to make a 90° angle or straight run T27 required for junction box feed Straight and right angle covers supplied 	<p>Dimensions</p> 
 <p>"T" Connector</p>	<p>Catalog # Finish Description</p> <p>R25 WH White R25 BL Black R25 SL Silver R25 BZ Bronze</p> <p>R25 RP WH White R25 RP BL Black R25 RP SL Silver R25 RP BZ Bronze</p>	<p>Description</p> <ul style="list-style-type: none"> Joins three track sections T27 required for junction box feed Same as above except designed for use in opposite polarity orientation compared to standard connectors See specification sheets for more details 	<p>Dimensions</p> 
 <p>Outlet Box Cover</p>	<p>Catalog # Finish Description</p> <p>T27 WH White T27 BL Black T27 SL Silver T27 BZ Bronze</p>	<p>Description</p> <ul style="list-style-type: none"> Use with R24 and R25 for outlet box electrical feed Includes nipple, locknut, and ground screw 	<p>Dimensions</p> 
 <p>Track Continuation Kit</p>	<p>Catalog # Finish Description</p> <p>R49 WH White R49 BL Black R49 SL Silver R49 BZ Bronze</p>	<p>Description</p> <ul style="list-style-type: none"> Two conduit adapters (one left R34 and one right R34) to continue track run around or thru obstructions Use with standard 1/2" electrical connectors 	<p>Dimensions</p> 

Current Limiting Feeds & Circuit Breakers

Current Limiting Feeds


	Catalog #	Finish	Track Type	Description	Dimensions
 <p>Mini End Feed</p>	RCLFM11 WH	White	1-Circuit	Mini End Feed	
	RCLFM11 BL	Black			
	RCLFM11 SL	Silver			
	RCLFM11 BZ	Bronze			
	RCLFM11 RP WH	White	1-Circuit	Same as above except	
	RCLFM11 RP BL	Black		designed for use in	
		RCLFM11 RP SL	Silver		opposite polarity orientation
		RCLFM11 RP BZ	Bronze		compared to standard feeds –
				see specification sheets for	
				more details	

	Catalog #	Finish	Track Type	Description	Dimensions
 <p>End Feed</p>	RCLF11 RP WH	White	1-Circuit	End Feed	
	RCLF11 RP BL	Black			
					

	Catalog #	Finish	Track Type	Description	Dimensions
 <p>In-Line Feed</p>	RCLF21 RP WH	White	1-Circuit	In-Line Feed	
	RCLF21 RP BL	Black			
					

Current Limiting Circuit Breakers - Order Separately

Example: **RCLF11 BL** and **TCLCB 5A BLCK**

	Catalog #	Dimensions	Descriptions	Wattage	Finish
	TCLCB 0.5A		0.5A Current Limiting Circuit Breaker	60W	WHT, BLCK
	TCLCB 1A		1A Current Limiting Circuit Breaker	120W	WHT, BLCK
	TCLCB 2A		2A Current Limiting Circuit Breaker	240W	WHT, BLCK
	TCLCB 3A		3A Current Limiting Circuit Breaker	360W	WHT, BLCK
	TCLCB 4A		4A Current Limiting Circuit Breaker	480W	WHT, BLCK
	TCLCB 5A		5A Current Limiting Circuit Breaker	600W	WHT, BLCK
	TCLCB 6A		6A Current Limiting Circuit Breaker	720W	WHT, BLCK
	TCLCB 7A		7A Current Limiting Circuit Breaker	840W	WHT, BLCK
	TCLCB 8A		8A Current Limiting Circuit Breaker	960W	WHT, BLCK
	TCLCB 10A		10A Current Limiting Circuit Breaker	1200W	WHT, BLCK
	TCLCB 12A		12A Current Limiting Circuit Breaker	1440W	WHT, BLCK
	TCLCB 14A		14A Current Limiting Circuit Breaker	1680W	WHT, BLCK

Current Limiting Feeds & Subpanels

Current Limiting Pendant Stem Kits

Current Limiting Pendant Stem Kits combine the functionality of pendant mounting with the ability to feed the track with current limiting in an attractive, integrated solution.





T-Bar Ceiling Mount

Catalog #	Finish
T90CLF 12IN BL	Black
T90CLF 12IN SL	Silver
T90CLF 12IN WH	White
T90CLF 18IN BL	Black
T90CLF 18IN SL	Silver
T90CLF 18IN WH	White
T90CLF 24IN BL	Black
T90CLF 24IN SL	Silver
T90CLF 24IN WH	White
T90CLF 36IN BL	Black
T90CLF 36IN SL	Silver
T90CLF 36IN WH	White
T90CLF 48IN BL	Black
T90CLF 48IN SL	Silver
T90CLF 48IN WH	White

Description

- Compatible with 15/16" flush T-bar ceilings
- 12", 18", 24", 36", 48" stem lengths
- Includes mounting plate, canopy, stem and wireway cover (order R38 track feed connector and current limiting circuit breaker separately – see page 115)

Dimensions




Rigid Ceiling Mount

Catalog #	Finish
T91CLF 12IN BL	Black
T91CLF 12IN SL	Silver
T91CLF 12IN WH	White
T91CLF 18IN BL	Black
T91CLF 18IN SL	Silver
T91CLF 12IN WH	White
T91CLF 24IN BL	Black
T91CLF 24IN SL	Silver
T91CLF 24IN WH	White
T91CLF 36IN BL	Black
T91CLF 36IN SL	Silver
T91CLF 36IN WH	White
T91CLF 48IN BL	Black
T91CLF 48IN SL	Silver
T91CLF 48IN WH	White

Description

- Compatible with 15/16" flush T-bar ceilings
- 12", 18", 24", 36", 48" stem lengths
- Includes mounting plate, canopy, stem and wireway cover (order R38 track feed connector and current limiting circuit breaker separately – see page 115)

Dimensions



Current Limiting Subpanel

The SilverBullet is a "sub-branch circuit current limiter" for track lighting that enforces a definite current limit to lower the VA rating of each track lighting circuit and meet code requirements. Use of a current limiting subpanel is often a more cost-effective method of employing current limiting, especially for applications with more than 10 circuits to limit.

See page 90 for more details.





Mounting Accessories

Pendant Stem Kits

Pendant Stem kits enable the track to be mounted at ideal heights, without having to lower the entire ceiling plane. Stems can be specified in a variety of different lengths and can be joined for higher ceiling applications.

	Catalog #	Finish	Description	Dimensions
 <p>T-Bar Pendant Stem Kit</p>	T90 12IN WH	White	<ul style="list-style-type: none"> Compatible with 15/16" flush T-bar ceilings 12", 18", 24", 36", 48" stem lengths Use two for 2', 4', or 6' track, or three for 8' track For electrical feed, order Wireway Cover T93 and R38 	
	T90 12IN BL	Black		
	T90 12IN SL	Silver		
	T90 12IN BZ	Bronze		
	T90 18IN WH	White		
	T90 18IN BL	Black		
	T90 18IN SL	Silver		
	T90 18IN BZ	Bronze		
	T90 24IN WH	White		
	T90 24IN BL	Black		
	T90 24IN SL	Silver		
	T90 24IN BZ	Bronze		
	T90 36IN WH	White		
	T90 36IN BL	Black		
	T90 36IN SL	Silver		
	T90 36IN BZ	Bronze		
T90 48IN WH	White			
T90 48IN BL	Black			
T90 48IN SL	Silver			
T90 48IN BZ	Bronze			

	Catalog #	Finish	Description	Dimensions
 <p>Rigid Ceiling Pendant Stem Kit</p>	T91 12IN WH	White	<ul style="list-style-type: none"> Compatible with rigid ceilings 12", 18", 24", 26", 48" stem lengths Use two for 2', 4', or 6' track, or three for 8' track For electrical feed, order Wireway Cover T93 and R38 	
	T91 12IN BL	Black		
	T91 12IN SL	Silver		
	T91 12IN BZ	Bronze		
	T91 18IN WH	White		
	T91 18IN BL	Black		
	T91 18IN SL	Silver		
	T91 18IN BZ	Bronze		
	T91 24IN WH	White		
	T91 24IN BL	Black		
	T91 24IN SL	Silver		
	T91 24IN BZ	Bronze		
	T91 36IN WH	White		
	T91 36IN BL	Black		
	T91 36IN SL	Silver		
	T91 36IN BZ	Bronze		
T91 48IN WH	White			
T91 48IN BL	Black			
T91 48IN SL	Silver			
T91 48IN BZ	Bronze			

	Catalog #	Finish	Description	Dimensions
 <p>Feed Wireway Cover</p>	T93 WH	White	<ul style="list-style-type: none"> Use one for each T90 or T91 when using stem for feeding track Feed at R38 or R24 Conceals electrical feed wires from stem to track 	
	T93 BL	Black		
	T93 SL	Silver		
	T93 BZ	Bronze		



Pendant Stem Kits



Mounting Accessories (cont)

Pendant Stem kits enable the track to be mounted at ideal heights, without having to lower the entire ceiling plane. Stems can be specified in a variety of different lengths and can be joined for higher ceiling applications.

Pendant Stem Support Kits





	Catalog #	Finish	Description	Dimensions
 <p>Pendant Stem Mechanical Support Kit</p>	T9091M 12IN WH	White	<ul style="list-style-type: none"> • For mechanical support only (no feed) 	
	T9091M 12IN BL	Black	<ul style="list-style-type: none"> • Suspends track from T-bar or rigid ceilings 	
	T9091M 12IN SL	Silver	<ul style="list-style-type: none"> • Offers simpler installation and a smaller ceiling footprint 	
	T9091M 18IN WH	White	<ul style="list-style-type: none"> • 12", 18", 24", 36", 48" stem lengths 	
	T9091M 18IN BL	Black	<ul style="list-style-type: none"> • Use two for 2', 4', or 6' of track or three for 8' and four for 12' of track 	
	T9091M 18IN SL	Silver	<ul style="list-style-type: none"> • Includes Mini-Canopy, pendant stem, 1-5/16" T-bar clip, drywall anchor and track mounting hardware 	
	T9091M 24IN WH	White		
	T9091M 24IN BL	Black		
	T9091M 24IN SL	Silver		
	T9091M 36IN WH	White		
	T9091M 36IN BL	Black		
	T9091M 36IN SL	Silver		
T9091M 48IN WH	White			
T9091M 48IN BL	Black			
T9091M 48IN SL	Silver			

	Catalog #	Finish	Description	
 <p>Pendant Stem Threaded Coupling</p>	T96 WH	White	<ul style="list-style-type: none"> • Enables multiple pendant stems to be joined for higher ceiling applications 	
	T96 BL	Black		
	T96 SL	Silver		
	T96 BZ	Bronze		




	Catalog #	Finish	Description	
 <p>Pendant Slope Ceiling Adapter</p>	T94 WH	White	<ul style="list-style-type: none"> • Permits pendant track stem to be hung vertically from sloped ceiling 	
	T94 BL	Black		
	T94 SL	Silver		
	T94 BZ	Bronze		

Mounting Accessories

Cable Suspension Kit



 <p>T-Bar/Rigid Ceiling Cable Suspension Kit</p>	Catalog #	Finish	Description	
	T595 48IN WH	White	<ul style="list-style-type: none"> Mechanical-only cable suspension kit for one-circuit or two-circuit track Adjustable 48" or 144" cable For use on 15/16" T-bar ceiling 	
	T595 48IN BL	Black		
	T595 144IN WH	White	<ul style="list-style-type: none"> Mechanical-only cable suspension kit for one-circuit or two-circuit track Adjustable 48" or 144" cable For use on rigid ceiling 	
T595 144IN BL	Black			
 <p>T-Bar/Rigid Ceiling Cable Suspension/Feed Kit</p>	Catalog #	Finish	Description	
	T596 48IN WH	White	<ul style="list-style-type: none"> Cable suspension kit with 48" or 144" electrical feed for one-circuit track For use on 15/16" T-bar ceiling 	
	T596 48IN BL	Black		
	T596 144IN WH	White	<ul style="list-style-type: none"> Cable suspension kit with 48" or 144" electrical feed for one-circuit track For use on rigid ceiling 	
	T596 144IN BL	Black		
	T598 48IN WH	White	<ul style="list-style-type: none"> Cable suspension kit with 48" or 144" electrical feed for one-circuit track For use on rigid ceiling 	
	T598 48IN BL	Black		
	T598 144IN WH	White		
T598 144IN BL	Black			



Mounting Accessories



 <p>T-Bar Attachment Clip</p>	Catalog #	Description		
	R37F	<ul style="list-style-type: none"> To attach track to inverted tee ceiling Use two for 2' or 4' track or three for 6' or 8' track R37F T-Bar Clip is compatible with flush tile 15/16" inverted T-bar ceiling R37D T-Bar Clip is compatible with drop tile 15/16" inverted T-bar ceiling R37916 T-Bar Clip is compatible with drop tile or flush tile 9/16" inverted T-Bar ceiling 		
	R37D			
	R37916			
T56 WH	Finish		Description	
T56 BL	White	<ul style="list-style-type: none"> Attaches solid 5/16" threaded rod to track Includes plastic cap, mounting bracket, and hardware Rod not supplied 		
T56 SL	Black			
T56 BL	Silver			
T56 BZ	Bronze			
 <p>Slope Ceiling Fixture Adapter</p>	Catalog #	Finish	Description	Dimensions
	T95 WH	White	<ul style="list-style-type: none"> Attaches to track, permitting Juno Trac-Master and Trac-Lites fixtures using the standard square Super Adapter to be hung vertically from sloped ceiling 90° maximum adjustment 	 <p>4 3/4" max.</p>
	T95 BL	Black		



Mounting Accessories

Mounting Accessories (cont)

 <p>Monopoint - Line Voltage</p>	Catalog #	Finish	Description	Dimensions
	R40N WH	White	• Accepts Juno Trac-Master & Trac-Lites 120V track	
	R40N BL	Black	• Mounts directly to outlet box	
	R40N BZ	Bronze		
	R40N SL	Silver		

 <p>Line Voltage Monopoint-Flush Mount</p>	Catalog #	Finish	Description	Dimensions
	T40F WH	White	• Mounts directly to 4" outlet box only	
	T40F BL	Black	• Accepts Juno Trac-Master & Trac-Lites 120V track fixtures using the standard square Super Adapter	


 <p>Line Voltage Duopoint</p>	Catalog #	Finish	Description	Dimensions
	T41N WH	White	• Mounts directly to outlet box	
	T41N BL	Black	• Accepts two Juno Trac-Master or Trac-Lites 120V track fixtures	

 <p>Weighted Base</p>	Catalog #	Finish	Description	Dimensions
	T42N WH	White	• Heavy base enables track fixture to be placed on a horizontal surface (i.e. floor, shelf) and aimed upwards	
	T42N BL	Black	• Accepts Juno Trac-Master & Trac-Lites 120V track fixtures	
			• Supplied with 8' cord and plug for portable use	

Extension Wands & Special Mounting Accessories

Line Voltage Extension Wands

Extension wands suspend fixtures precisely where they are needed without lowering the track section. On/Off switch is standard. Line voltage extension wands suspend all Juno line voltage track fixtures from all 120V Juno Trac. Two extension wand types are available: one designed for use with the standard square Super Adapter found on most Trac-Master and Trac-Lites fixtures and one designed for use with the wide adapter found on some track fixtures such as T255L, T265L and T267L. Always confirm the fixture adapter type before specifying an extension wand to ensure compatibility. May also be used with Monopoints designed to accept Juno 120V track fixtures. Constructed of 1/2" rigid tubular steel and Lexan® plastic.



Line Voltage

Line Voltage Extension Wands			Overall Length
Super Adapter Catalog #	Finish		
TEW 12IN WH	White		13 1/2"
TEW 12IN BL	Black		
TEW 18IN WH	White		19 1/2"
TEW 18IN BL	Black		
TEW 18IN SL	Silver		
TEW 24IN WH	White		25 1/2"
TEW 24IN BL	Black		
TEW 24IN SL	Silver		
TEW 36IN WH	White		37 1/2"
TEW 36IN BL	Black		
TEW 48IN WH	White		49 1/2"
TEW 48IN BL	Black		
TEWS WH*	White		28 1/2"
TEWS BL*	Black		

* 24IN wand with slope adapter on top.

Miscellaneous Track Accessories




Pendant Adapter

Catalog #	Finish
T31N WH	White
T31N BL	Black
T31N SL	Silver

Description

- Adapts swag or chain-hung fixture to track
- Includes strain relief for 3-wire cord (replaces chain loop)
- Chain installation accepts wire diameters up to 0.270" and supports up to 15 lbs.; strain relief installation requires Type SVT 18/3 3-wire cord and supports up to 5 pounds.
- UL Listed
- 5A max

Dimensions



Note: T31N is available with GTYPE, HTYPE and LTYPE Alternate Mounting Adapters – see specification sheet for details.




Planter or Utility Hook

Catalog #	Finish
T32 WH	White
T32 BL	Black

Description

- Supports up to 25 lbs.
- Not UL Listed

Dimensions




Outlet Adapter

Catalog #	Finish
T33 WH	White
T33 BL	Black
T33 SL	Silver

Description

- Provides electrical receptacle
- Not UL Listed
- 7A max

Dimensions



Coil Cord Calmp-Ons & Outrigger Mounting Bracket

Coil Cord Clamp-Ons with Monopoint

Coil cord clamp-ons provide an innovative way to mount fixtures to pipe and flat surfaces up to 1 1/2" thick. Designed with futuristic styling in mind for dynamic displays and special mounting situations.



Track Line Voltage Coil Cord Clamp-On

Super Adapter

Catalog

T132 WH

T132 BL

Finish


White

Black

Description

- Attaches to Juno 120V Trac-Master & Trac-Lites 120V and Monopoints
- Accepts Juno Trac-Master & Trac-Lites 120V track (confirm fixture adapter type before specifying to ensure compatibility)
- Includes On/Off switch
- 2' coil cord extends to 5'

Dimensions



Plug-In Line Voltage Coil Cord Clamp-On

Super Adapter

Catalog

T133 WH

T133 BL

Finish


White

Black

Description

- With coil cord and male plug (for standard 120V receptacle)
- Accepts Juno Trac-Master & Trac-Lites 120V track fixtures (confirm fixture adapter type before specifying to ensure compatibility)
- Includes On/Off switch
- 2' coil cord extends to 5'

Dimensions



Outrigger Track Mounting Bracket (non-electrified)



Outrigger Track Mounting Bracket

Catalog

T47 WH

T47 BL

Finish

White

Black

Description

- For mounting track out from wall
- Use two for 2', 4' or 6' track sections, three for 8' sections, four for 12' sections
- Order track and track connectors separately
- For portable electric feed, use R22 or R122 Cord Set
- For permanent wiring, use R38 Live End Feed

Dimensions

24"L x 8"H

Track Kits



Track Kits

Packed to go. The most popular models supplied in simple-to-install pre-packaged kits.

Line Voltage Conical LED Track Kits



Description

- Kit includes three (3) universal beam R600L 10W LED track fixtures, one 4' Trac-Lites track section, one floating electrical feed and mounting hardware.
- Kits are available in all R600L CCTs, CRIs and finishes to suit any retail, commercial or residential application.

Ordering Information

Ordering Example: R4K3600L 27K 90CRI PDIM UNF BZ

Series	Color Temperature	Color Rendering Index	Dimming Compatibility	Distribution	Finish
R4K3600L Trac-Lites R600LTrac Kit	27K 2700K	80CRI 80 CRI	PDIM Phase Dimmable	UNF Universal - Narrow Flood, Flood	BL Black
	30K 3000K	90CRI 90 CRI			SL Silver
	35K 3500K	97CRI¹ 97 CRI			WH White
	40K 4000K				

¹ Special order - may have extended lead-times or order minimums; not available in 35K.

Line Voltage Flared Step Cylinder Track Kit



Catalog #
R4K3551 WH

Finish
White

Description

- 50W max. PAR20 lamps
- One 4' section of track, floating feed, and three flared step cylinder fixtures (R551 WH)





Juno[®] Trac-Lites[™]

Juno Trac-Lites bring you all the style, quality and lighting performance Juno is famous for at affordable prices that can be tailored to any budget.

Juno Trac-Lites offer a total system, featuring a wide assortment of low voltage and line voltage track fixtures, system components and track kits. Track fixtures are available in all the popular classics and in exciting contemporary designs, from flares and open backs to cylinders, bells, and cubes.

For added versatility, all Trac-Lites fixtures are compatible with Juno Trac-Master[™] Trac systems and all Juno Trac-Master fixtures may be used on Trac-Lites Trac systems.





Juno[®] Trac-Lites[™] System



©2019 Acuity Brands Lighting, Inc. The marks appearing in this catalog are trademarks of Acuity Brands Lighting, Inc. Products shown in this brochure may be covered by U.S. and international patents and patents pending. Specifications subject to change without notice. Printed in the U.S.A.