

Trac-Lites[™] 10W LED R600-L Series

Innovative LED lighting in an economical design

The Juno[®] Trac-Lites R600L Series features stylish – yet economical – LED track fixtures, with simple and timeless aesthetics. Its high performance LED array provides outstanding reliability, performance and color quality/consistency. R600L Series fixtures are compatible with Juno Trac-Lites and Trac-Master[™] Trac and system components.

Features:

2700K, 3000K, 3500K or 4000K white phosphor high performance LEDs

80+ CRI standard, optional high 90+ CRI or 97+ CRI versions

Integral driver to minimize overall fixture footprint

Proprietary, interchangeable lenses and TIR optics in factory-configured spot, narrow flood or flood beam spreads

350° horizontal coverage, **90°** vertical aiming capability

Designed for greater than 50,000 hour operating life

Dimmable - see specification sheet for compatible dimmers

ENERGY STAR* Certified and DesignLights Consortium* Qualified

Noted versions can be used to comply with **California Title 24**, **Part 6** high efficacy LED light source requirements

5-year warranty from the date of purchase





Juno[®] Trac-Lites[™] 10W LED R600L Series

| Ordering Information | | | | | | | | | | | | | | | | |
|----------------------|--|---|--|----|------------|--------------------------|----------------------------------|--|---|------|------------------|--|--|----------------------|------------------------------------|--|
| | Ordering Example: R600L G2 27K 80CRI PDIM NFL BL | | | | | | | | | | | | | | | |
| Series Mo | | Mounting | Mounting Adapter Type | | Generation | | Color Tempertaure | | Color Rendering Index | | Dimming | | Beam Distribution | | Finish | |
| R600L | 10W LED | (Blank) GTYPE ¹ HTYPE ¹ LTYPE ² | Universal 120V Trac Adapter G-Type Trac Adapter H-Type Trac Adapter L-Type Trac Adapter | G2 | Gen 2 | 27K 30K 35K 40K | 2700K 3000K 3500K 4000K | | 80 CRI Minimum 90 CRI Minimum 970 CRI Minimum 7K, 30K and er minimums and -times may apply) | PDIM | Phase Dimming | SP NFL FL UNF (Includes and flood | Spot Narrow Flood Flood Universal Beam s narrow flood d lenses) | BL BZ SL WH | Black Bronze Silver White | |

* Can be used to comply with California Title 24, Part 6 high efficacy LED light source requirements.

¹ GTYPE and HTYPE adapters available in BL, SL, and WH finish only.

² LTYPE adapter available in BL and WH finish only.

Dimensions



Juno Trac-Lites R600L LED Track Kits

These all-inclusive track kits are the perfect solution for residential installations, or commercial/retail applications that require just a few track fixtures mounted on a small section of track. Each kit includes three universal beam R600L LED track fixtures, one 4' Trac-Lites track section, one floating electrical feed and mounting hardware. Kits are available in all R600L CCTs, CRIs and finishes to suit any retail, commercial or residential application.



| Ordering Information | | | | | | | | | | | | | | |
|----------------------|---|--------------------------|----------------------------------|-----------------------|--|---------|---------------|-----------------------------|----------------|----------------------|------------------------------------|--|--|--|
| | Ordering Example: R4K3600L 27K 90CRI PDIM UNF BZ | | | | | | | | | | | | | |
| Series | | Color Tempertaure | | Color Rendering Index | | Dimming | | Beam Distribution | | Finish | | | | |
| R4K3600L | R600L Trac Kit (3) 10W LED Heads and (1) 4' Track | 27K 30K 35K 40K | 2700K 3000K 3500K 4000K | | 80 CRI Minimum 90 CRI Minimum 970 CRI Minimum 7K, 30K and 40K only; order d extended lead-times may apply) | PDIM | Phase Dimming | UNF (Includes lenses) | Universal Beam | BL BZ SL WH | Black Bronze Silver White | | | |

* Can be used to comply with California Title 24, Part 6 high efficacy LED light source requirements.



