



Catalog Number
Notes
Type

Contractor Select™

# 4RLA

## 4" LED Retrofit Modules

The Juno® Basics Series™ 4RLA Adjustable is designed for vertical aiming up to 35° and is offered in 65° wide flood optic. In this all in one design, the LED light engine is mounted directly to the housing for superior thermal management and the gimbal trim with built-in flange is made of durable die cast aluminum. Trims can be used to comply with Title 24, JAB8 high efficacy light source requirements and include a 5-year limited warranty.

**FEATURES:**

- Rated for use in IC or non-IC housings including IC1 LEDT24; IC1R LEDT24
- 2700K or 3000K color temperatures, 90+ CRI
- Dimmable to 5% with many incandescent, magnetic low voltage or electronic low voltage box dimmers



Catalog Number	UPC	Description	Replaces Up To	Lumens	Input Watts	CCT	CRI	Voltage	Finish	Dimming Protocol	Pallet qty.
4RLA G2 06LM 27K 90CRI WFL 120 FRPC WH	661209652560	4" Basics Series™ Adjustable LED Retrofit Trim Wide Flood	50W	600	10.5W	2700K	90	120V	White	Forward & Reverse Phase Cut	648
4RLA G2 06LM 30K 90CRI WFL 120 FRPC WH	661209652584	4" Basics Series™ Adjustable LED Retrofit Trim Wide Flood	50W	600	10.5W	3000K	90	120V	White	Forward & Reverse Phase Cut	648



## Specifications

### LED RETROFIT ADJUSTABLE TRIM:

Cast aluminum trim with white gimbal and flange. All-in-one design where LED light engine mounts directly to trim for ease of installation into existing 4" recessed housings with medium base sockets • Up to 35° vertical adjustment • Provided with push-in friction springs.

### LED LIGHT ENGINE:

LEDs mounted directly to aluminum housing designed to provide superior thermal management and ensure long life • 2700K or 3000K LED color temperature • 90 CRI minimum • Accommodates 120 volts AC at 60Hz • Dimmable with most standard incandescent, magnetic low voltage and electronic low voltage dimmers • For a list of compatible dimmers, see [JUNORETROBASICS-DIM](#).

### ELECTRICAL CONNECTIONS:

Trim features quick connect plug installed as standard for installation into IC1 LEDT24 and IC1R LEDT24 housings with mating connector • Trim ships with a medium base socket adapter whip for installation into 4" incandescent housings with medium base sockets.

### OPTICAL SYSTEM:

Trims are offered in a wide flood beam pattern • LED source concealed with lensed optic.

### LIFE:

Rated for 50,000 hours at 70% lumen maintenance.

### LABELS:

Certified to the high efficacy requirements of California T24 • UL and cUL classified for use with most standard UL listed 4" recessed incandescent housings and Juno IC1 LEDT24 and IC1R LEDT24; see below for specific compatibility requirements • Damp location.

### TESTING:

All reports are based on published industry procedures; field performance may differ from laboratory performance.

### COMPATIBLE HOUSINGS:

The 4RLA G2 retrofit adjustable trim is compatible with most 4" recessed housings measuring at least 4" high with an inside diameter between 4" and 4-1/2".

### WARRANTY:

5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at:

[www.acuitybrands.com/support/warranty/terms-and-conditions](http://www.acuitybrands.com/support/warranty/terms-and-conditions)

**Note:** Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

## Dimensions

