



TRAC 12 LED CYLINDRA™ SPOTLIGHT 12-VOLT AC

TL252L



Project: _____

Fixture Type: _____


Location: _____

Contact/Phone: _____

PRODUCT DESCRIPTION

The contemporary styling of the Cylindra LED enables it to subtly enhance practically any decor without diverting attention from the surrounding environment. Soft curved surfaces combine with clean, crisp edges to provide a uniquely attractive aesthetic. The Trac 12 Cylindra™ 13W LED spotlight approximates the light output and distribution of 75W MR16 halogen lamps, utilizing less than 1/5 of the energy and having a rated life of 50,000 hours. It is available in 2700K, 3000K, 3500K and 4000K color temperatures with a minimum 80 CRI. An optional high CRI version is available in 2700K or 3000K with a minimum 90 CRI. The white-light Cylindra LED is compatible with standard Trac 12 and Trac 12/25 trac, operating with 12V AC power. The TL252L can be placed anywhere along the Trac, and the trac can be cut-to-length during installation, making it an economical and flexible accent lighting choice. Cylindra's integral, bayonet-mounted accessory holder accommodates one accessory if desired.

DIMENSIONS



PRODUCT SPECIFICATIONS

LED Single Cree LED array provides outstanding reliability, performance and color quality/consistency • 2700K, 3000K, 3500K or 4000K white phosphor high performance LEDs • Chromaticity range within a 2-step MacAdam Ellipse • Minimum 80 CRI on standard versions • Optional high CRI 2700K or 3000K versions offer 90 CRI minimum.

Driver Concealed in rear of fixture housing to minimize overall fixture footprint • Requires 12VAC LED-compatible power source (order separately – see Transformers/Monopoints).

Optics Interchangeable computer-designed custom TIR optics available in three factory-configured beam spreads • One TIR optic provided with fixture (as specified in catalog number) • Accessory optics available to enable beam changes in the field • Beam patterns can also be altered as desired using a variety of available light control accessories.

Accessory Holder Integral to fixture design • Die cast aluminum construction • Precision bayonet mounting • Accommodates one accessory if desired.

Construction Die cast aluminum housing provides outstanding thermal management of LED, yielding 70% average lumen maintenance at 50,000 hours of operation • Fashionable, elegant design complements any decor • Available in white and black painted finishes.

Aiming 90° vertical aiming capability and 360° horizontal coverage.

Electrical Contacts Beryllium copper.

Transformers/Drivers Compatible with all Juno 12VAC transformers and Trac 12 Monopoints designated as LED-compatible – refer to transformer specification sheets for details.

Dimming May be dimmed with dimmers tested and qualified by Juno for use with the non-resistive TL252L Series load – see transformer/driver specifications for compatible dimmers • Color temperature remains constant over dimming range • Consult factory for additional information.

Government Procurement

BAA – Buy America(n) Act: Product qualifies as a domestic end product under the Buy American Act as implemented in the FAR and DFARS. Product also qualifies as manufactured in the United States under DOT Buy America regulations.

BABA – Build America Buy America: Product qualifies as produced in the United States under the definitions of the Build America, Buy America Act.

Please refer to www.acuitybrands.com/buy-american for additional information.

Warranty Warranty period is 5 years on LED components from date of purchase • Standard Juno Lighting Group product guarantee terms and conditions apply • Continuously operating the TL252L above 12VAC will void the warranty • This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed.

Labels UL/cUL listed for use with Trac 12 and Trac 12/25 trac.

Specifications subject to change without notice • Union made • Assembled in U.S.A.

ORDERING INFORMATION

Ordering Example: TL252L 27K 80CRI NFL BL

Fixture Type	Color Temperature	Color Rendering Index	Beam Spread	Finish
TL252L Cylindra LED	27K 2700K 30K 3000K 35K 3500K 40K 4000K	80CRI 80 CRI 90CRI 90 CRI (2700K & 3000K only)	SP Spot NFL Narrow Flood FL Flood	BL Black WH White

ACCESSORIES

Cat. No.	Description	Cat. No.	Description	Cat. No.	Description
HCLBL 200	Hexagonal Cell Louver - Black	DIFF 200	Diffuse Glass Lens	TIR2 SPT	TIR Optic - Spot
SNOOTBL 200	Snoot - Black	SOLITE 200	Uniformity Lens (Solite)	TIR2 NFLD	TIR Optic - Narrow Flood
CGF 200	Color Glass Filter	PRISM 200	Prismatic Spread Glass Lens	TIR2 FLD	TIR Optic - Flood
DGF 200	Dichroic Glass Filter	LSPREAD 200	Linear Spread Glass Lens		
DCCF 200	Dichroic Color Correction Filter ¹	T74BL 175	Barn Doors - Black		

See specification sheet [D1.2.2](#) for details. Other accessories can be found on specification sheet [D3.1.0](#).

¹DCCF 200 HAL2700 corrects 3000K color to approximately 2700K and 4000K color to approximately 3400K.





TRAC 12 LED CYLINDRA™ SPOTLIGHT 12-VOLT AC TL252L

PERFORMANCE DATA¹


Catalog Number	Input Voltage	Watts (Typical)	Lumens	Efficacy (LPW)	Rated Life (Hours)
TL252L 27K 80CRI SP	12V	13W	776	60	50,000
TL252L 27K 80CRI NFL	12V	13W	797	61	50,000
TL252L 27K 80CRI FL	12V	13W	856	66	50,000
TL252L 27K 90CRI SP	12V	13W	576	44	50,000
TL252L 27K 90CRI NFL	12V	13W	591	45	50,000
TL252L 27K 90CRI FL	12V	13W	635	49	50,000
TL252L 30K 80CRI SP	12V	13W	834	64	50,000
TL252L 30K 80CRI NFL	12V	13W	857	66	50,000
TL252L 30K 80CRI FL	12V	13W	920	71	50,000
TL252L 30K 90CRI SP	12V	13W	617	47	50,000
TL252L 30K 90CRI NFL	12V	13W	634	49	50,000
TL252L 30K 90CRI FL	12V	13W	681	52	50,000
TL252L 35K 80CRI SP	12V	13W	893	69	50,000
TL252L 35K 80CRI NFL	12V	13W	917	71	50,000
TL252L 35K 80CRI FL	12V	13W	985	76	50,000
TL252L 40K 80CRI SP	12V	13W	834	64	50,000
TL252L 40K 80CRI NFL	12V	13W	857	66	50,000
TL252L 40K 80CRI FL	12V	13W	920	71	50,000

CBCP • Centerbeam candlepower
FC • Footcandles at beam center (aim point)

In vertical aiming applications, aim point (X) is determined by dividing distance from the wall (D) by the tangent of the desired aim angle (A) (0.5774 for 30°, 1.0 for 45°, 1.732 for 60°).



¹Performance data, including Rated Life, is based on measurements of an individual fixture operating in a 25 °C ambient. In practice, multiple fixtures used in a system will average slightly lower power consumption due to voltage drop within the system.
Note: For operation at 11.5 volts multiply Lumens by 0.94.



Fixture	Beam Type	Beam Spread	Rated Life	CBCP	0°		30°			30°				45°				60°							
					MH	FC	L	W	FC	L	W	D	FC	X	L	W	FC	X	L	W	D	FC	X	L	W
Cylindra 13W LED, 3000K, 80CRI Spot	S	15°	50000	7592	6	211	1.5	1.5	137	2.1	1.8	3	105	5.2	3.2	1.5	298	3.0	1.6	1.1	6	137	3.5	2.1	1.8
					8	119	2.0	2.0	77	2.7	2.4	4	59	6.9	4.3	2.0	168	4.0	2.1	1.4	8	77	4.6	2.7	2.4
					10	76	2.6	2.6	49	3.4	3.0	5	38	8.7	5.4	2.6	107	5.0	2.6	1.8	10	49	5.8	3.4	3.0
					12	53	3.1	3.1	34	4.1	3.6	6	26	10.4	6.5	3.1	75	6.0	3.1	2.2	12	34	6.9	4.1	3.6
					14	39	3.6	3.6	25	4.8	4.1	7	19	12.1	7.5	3.6	55	7.0	3.6	2.5	14	25	8.1	4.8	4.1
Cylindra 13W LED, 3000K, 80CRI Narrow Flood	N	27°	50000	3473	5	139	2.4	2.4	90	3.3	2.8	2	109	3.5	4.7	2.0	307	2.0	2.1	1.4	4	141	2.3	2.7	2.3
					6	96	2.9	2.9	63	4.0	3.4	3	48	5.2	7.1	2.9	136	3.0	3.1	2.1	5	90	2.9	3.3	2.8
					7	71	3.4	3.4	46	4.6	3.9	4	27	6.9	9.5	3.9	77	4.0	4.1	2.8	6	63	3.5	4.0	3.4
					8	54	3.9	3.9	35	5.3	4.5	5	17	8.7	11.9	4.9	49	5.0	5.2	3.4	7	46	4.0	4.6	3.9
					9	43	4.4	4.4	28	6.0	5.1	6	12	10.4	14.2	5.9	34	6.0	6.2	4.1	8	35	4.6	5.3	4.5
Cylindra 13W LED, 3000K, 80CRI Flood	F	41°	50000	1797	3	200	2.2	2.2	130	3.1	2.6	1.5	100	2.6	7.6	2.2	282	1.5	2.6	1.6	3	130	1.7	3.1	2.6
					4	112	3.0	3.0	73	4.1	3.4	2.0	56	3.5	10.1	3.0	159	2.0	3.4	2.1	4	73	2.3	4.1	3.4
					5	72	3.7	3.7	47	5.2	4.3	2.5	36	4.3	12.6	3.7	102	2.5	4.3	2.6	5	47	2.9	5.2	4.3
					6	50	4.5	4.5	32	6.2	5.1	3.0	25	5.2	15.2	4.5	71	3.0	5.2	3.1	6	32	3.5	6.2	5.1
					7	37	5.2	5.2	24	7.3	6.0	3.5	18	6.1	17.7	5.2	52	3.5	6.0	3.7	7	24	4.0	7.3	6.0

For 2700K fixtures, use 0.93 multiplier; for 2700K 90CRI fixtures, use 0.69 multiplier.
For 3000K 90CRI fixtures, use 0.74 multiplier; for 3500K fixtures, use 1.07 multiplier.
For 4000K fixtures, use 1.00 multiplier.