

### **FEATURES & SPECIFICATIONS**

#### **INTENDED USE**

Provides general illumination in residential and light commercial applications. Ideal for use in workshops, utility rooms, and garages.

#### CONSTRUCTION

Constructed of a metal housing with decorative plastic end caps and a pull chain for easy on/off operation. The white acrylic lens provides even illumination on surfaces where tasks are performed. Shoplights are designed for suspended installation-model 1290L NST with mounting chains, and adjustable steel cables. 1290L can be installed with traditional installation or at a 30° angle to project light onto larger area. Available in all white body/white ends with 5′ white cord and plug.

#### **ELECTRICAL**

LEDs have a 50,000 hour L70 rated life. Provides a cool color temperature of 4000K with a CRI of 83. Starts reliably down to  $0^{\circ}$  F.

Model 1290L NST produces 3133 lumens, Standard input=28.24 watts, 110 lumens per watt.

Actual wattage may differ by  $\pm -5\%$  when operating at 120V  $\pm -10\%$ .

Standard with 120V driver (120V, 60Hz).

#### INSTALLATION

Includes 9 1/2" mounting chains and S-hooks.


#### LISTINGS

UL listed to US and Canadian safety standards.


#### WARRANTY

3-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at: <a href="https://www.acuitybrands.com/CustomerResources/Terms">www.acuitybrands.com/CustomerResources/Terms</a> and conditions.aspx

NOTE: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25°C. Specifications subject to change without notice.



All dimensions are inches (centimeters) unless otherwise indicated.



**Indoor General Purpose** 



ORDERING INFORMATION For shortest lead times, configure product using <b>bolded options</b> .		Example: 1290L
Series	Finish	
1290L NST 4' LED Shop Light	White housing with white ends and 5' white cord and plug	

DECORATIVE RESIDENTIAL LED SHOPLIGHT

# **LED Shoplight**

## **PHOTOMETRICS**

Full photometric data report available within 2 weeks from request. Consult factory. Actual performance may differ as a result of end-user environment and application.

## **LIGHTING FACTS**

