

Catalog Number
Notes
Type

## FEATURES & SPECIFICATIONS

**INTENDED USE** — The OneUp™ recessed direct-wire LED downlight includes integrated junction box, trim, pre-installed non-metallic bushings and 3-port push wire quick connectors in one package. The OneUp is the most economical means to create a well lit environment with exceptional energy efficiency and near zero maintenance.

**CONSTRUCTION** — Aluminum die cast, adjustable gimbal trim. Integrated galvanized steel junction box with captive door for easy access. Suitable for daisy chaining (pulling wires). Available in 3000K color temperature LEDs.

**OPTICS** — Round adjustable gimbal with 180 degrees of rotation and 35 degrees of adjustable tilt in both directions. Diffused lens provides even light distribution for general illumination, equivalent to 65W incandescent flood lamp. Wide flood beam angle at >90°. CRI >90. Maintains at least 70% light output for 50,000 hours.

**INSTALLATION** — Tool-less installation. Secure trim retention with two side-mounted spring clips for easy installation in plaster, sheet rock, or plywood ceilings. The integrated junction box - with pre-installed non-metallic bushing - allows non-metallic cable to be fed through without the hassle of knockouts. The captive junction box door provides easy access to pre-installed 3-port push wire quick connectors for straight-forward wiring. Rated for Type IC installations. Maximum of 4 No. 12AWG through branch circuit conductor suitable for 90°C permitted in box. Ground wire provided.

**ELECTRICAL SYSTEM** — LED module with high-efficiency on board driver. Dimming down to 10%. For compatible dimmers, refer to: Compatible dimmers chart.


Actual wattage may differ by +/-5% when operating at 120V +/-10%.

**LISTINGS** — ETL certified to US and Canadian safety standards. Can be used to comply with California Title 24 Part6 High Efficacy LED Light Source Requirements. ENERGY STAR® certified. Damp location listed.

**WARRANTY** — 5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at: [www.acuitybrands.com/support/warranty/terms-and-conditions](http://www.acuitybrands.com/support/warranty/terms-and-conditions)

**Note:** Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

Specifications	
Aperture:	3-1/8" (80.0)
Overlap Trim:	7-1/4" (184.0)
Height:	4-7/8" (122.3)
Ceiling Opening:	4-7/8" (122.3)
Min Ceiling Thickness:	1/2" (12.7)
Max Ceiling Thickness:	1-1/2" (38.1)
All dimensions are inches (millimeters).	



Direct-Wire LED Recessed Downlight

# 6JBK ADJ

IC  
Remodel

### ORDERING INFORMATION

Ci Code	Catalog Number	Description
*259WVU	6JBK ADJ 30K 90CRI MW M6	Canless Kit 6" Baffle, Adjustable, Round, 3000K CCT, 10.8W, 830L, 90CRI, Matte White
*260EFY	6JBK ADJ 30K 90CRI ORB M6	Canless Kit 6" Baffle, Adjustable, Round, 3000K CCT, 10.8W, 830L, 90CRI, Oil Rubbed Bronze

<b>Accessories:</b> Order as separate catalog number.	
OUIBK643 PAN U	Universal Construction Pan




**Notes**  
1 Total System Delivered Lumens.

# 6JBK ADJ OneUP™ Direct Wire LED

## PHOTOMETRICS

Distribution Curve	Distribution Data	Output Data	Coefficient of Utilization	Illuminance Data at 30" Above Floor for a Single Luminaire
--------------------	-------------------	-------------	----------------------------	--

6JBK ADJ 30K, 3000 K LEDs, input watts: 10.8, delivered lumens: 865, LM/W=76.8, test no. ISF 35027



## ENERGY DATA

6" ADJUSTABLE GIMBAL ENERGY DATA	
Color Temperature	3000K
Lumens	830
CRI	90
Lumens/Watt	76.85
Min. starting temperature	-18°C (-0°F)
EMI/RFI	FCC Title 47 CFR, Part 15, Class B
Sound rating	Class A Standards
Input voltage	120V AC
Min. power factor	0.9
Input frequency	50/60HZ
Rated wattage	10.8W
Input power	10.8W
Input current	0.09A

## DIMMER COMPATIBILITY

COMPATIBLE DIMMERS				
Lutron	Leviton	Pass & Seymour	Synergy/Leviton	Sensorswitch
DV-603P-LA	6633-PA	HCL453PTCCCV6	ISD 600 I 120 / IPI06	nSP5 PCD 2W
CT-603PR-WH	6615-P	LS 603 PWV	ISD 1000 I 120 / IPI10	nSP5 PCD ELV 120
DVELV-300P			ISD 400 ELV 120 / IPE04	
300P SELV				
DV-600P				
NTELV-300P				
NLV-600				
Caseta PD-6WCL dimmer (requires Lutron Smart Bridge L-BDG2-WH which is sold separately from the dimmer)				

## LIGHTING FACTS

Lithonia Lighting

<b>Light Output (Lumens)</b>	<b>830</b>
<b>Watts</b>	<b>10.8</b>
<b>Lumens per Watt (Efficacy)</b>	<b>76.85</b>

<b>Color Accuracy</b>	<b>90</b>
Color Rendering Index (CRI)	

<b>Light Color</b>	<b>3000 (Bright White)</b>
Correlated Color Temperature (CCT)	

2700K    3000K    4500K    6500K

All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit [www.lightingfacts.com](http://www.lightingfacts.com) for the Label Reference Guide.

Registration Number: NJSM-RBP1HK (7/20/2017)  
Model Number: 6JBK ADJ 30K 90CRI  
Type: Luminaire - Downlight