



Catalog Number
Notes
Type

Contractor Select™

IC23 LEDT24

6" Housings for LED Retrofit Trims

The Juno® 6-inch LED quick connect housing for use with Juno retrofit LED trim modules offers an energy-efficient, Air-Loc® sealed housing that stops ex-filtration and infiltration of air, reducing heating and cooling costs without extra gaskets. The IC-rated housing can also be completely covered with insulation.

FEATURES:

- Features non-screw base 120V plug-in quick connector
- Compatible with Juno retrofit LED trim modules
- Can be used to comply with Title 24, JA8 high efficacy light source requirements



Catalog Number	UPC	Description	Socket	Voltage	Pallet qty.
IC23 LEDT24	661209311061	6" New Construction IC Housing for LED Retrofit Trims	Quick Connector (No Socket)	120V	120



Specifications

ELECTRONIC CONNECTIONS:

Features non-screw base 120V plug-in connector • Compatible with Juno retrofit LED trim modules.

SOCKET:

Medium base porcelain with nickel-plated copper screw shell • Floating socket with spring attaches to trim for installation.

LABELS:

UL listed for through-branch wiring, and damp locations • Meets high efficacy requirements of California T24.

TESTING:

All reports are based on published industry procedures; field performance may differ from laboratory performance.

REAL NAIL 3 BAR HANGERS:

Telescoping, Patented (US Patent D552,969) Real Nail 3 system permits quick placement of housing anywhere within 24" O.C. joists or suspended ceilings • Integral T-bar notch and clip secures housing in suspended ceiling grid – no accessory clips required • 24" expansion stop allows quick placement of fixture in standard grid spacing • Bars scored in two locations for fast, clean breaking, allowing housing installation in tight applications • Bars captive to mounting frame • Edge-mounted for extra strength • Captive bugle-headed ring shank nail for quick one-step installation and easy removal with claw hammer for fixture relocation • Quick-Loc slot (location identified on the mounting frame) and oversized locking set screw lock fixture in position • Bar hanger foot contoured to align to bottom of construction joist • Alternate mounting holes included.

JUNCTION BOX:

Pre-wired junction box provided with (5) 1/2" and (1) 3/4" knockouts, (4) Non-metallic sheathed cable connectors and ground wire, U.L. listed/CSA certified for through-branch wiring, maximum 8 No. 12 AWG 90° C branch circuit conductors (4 in, 4 out) • Junction box provided with removable access plates • Knockouts equipped with pryout slots.

HOUSING:

IC housing, .032" aluminum sealed for Air-Loc Compliance • 22-gauge die-formed galvanized steel mounting frame • Rough-in section (junction box, mounting frame, housing and bar hangers) fully assembled for ease of installation • Sight lines embossed on mounting frame to allow for easy viewing when aligning fixtures • Housing is vertically adjustable to accommodate up to a 1" ceiling thickness.

WARRANTY:

1-year limited warranty. Complete warranty terms located at:

www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx

Note: Actual performance may differ as a result of end-user environment and application.

All values are design or typical values, measured under laboratory conditions at 25 °C.

Specifications subject to change without notice.

Dimensions

