



Catalog Number
Notes
Type

Contractor Select™

FMML 13

Versi Lite™ LED Flush Mount



Available in 13" round, the LED Versi Lite Flush Mount offers an energy-efficient lighting solution for an array of indoor and outdoor residential and light commercial spaces. With a 50,000 hour maintenance-free life, the Versi Lite delivers reliability along with bright, high quality illumination. Ideal for use in closets, foyers, hallways, bedrooms, offices, utility work areas, stairways, and many other rooms in the house.

FEATURES:

- Available in 4000K color temperature
- Dimmable to 10% on most standard triac dimmers



Catalog Number	UPC	Description	Replaces up to	Lumens	Input Watts	CCT	CRI	Voltage	Pallet qty.
FMML 13 840	888791432954	13" Versi Lite	2-75W Incandescent	2,000	28W	4000K	80	120V	120

More configurations are available. [Click here](#) or visit www.acuitybrands.com and search for FMML 13 & FMML 7



Specifications

INTENDED USE:

Provides general illumination in commercial and residential applications. Ideal for use in closets, foyers, hallways, corridors, bedrooms, offices, utility work areas, outdoor covered areas, stairways and much more. Suitable for use within closet storage spaces when installed per NEC requirements.

CONSTRUCTION:

This contemporary shaped fixture features a matte white acrylic diffuser with a robust aluminum housing.

OPTICS:

Produces the following lumens at 50,000 hours life (WH finish):
4000 K: 1985 lumens (13")

ELECTRICAL:

Fixture operates at 120 volts, 60 Hz.
13" Round standard input = 28 watts, 71 lumens per watt. 7".
Works with most standard incandescent dimmers.

LISTINGS:

CSA certified for sale in the USA and Canada. Also certified for Damp Location. ENERGY STAR® certified. Round Versi U.S. Patent No. D691,763


WARRANTY:

5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at:
www.acuitybrands.com/support/warranty/terms-and-conditions

Note: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

Dimensions

13"
Height: 2-1/2 (6.4)
Width: 13 (33.0)
Weight: 3.2lbs



All dimensions are inches (centimeters) unless otherwise indicated.