

| |
|----------------|
| Catalog Number |
| Notes |
| Type |

FEATURES & SPECIFICATIONS

INTENDED USE

Suitable for emergency lighting applications such as stairways and hallways.

Certain airborne contaminants can diminish the integrity of acrylic and/or polycarbonate.
[Click here for Acrylic-Polycarbonate Compatibility table for suitable uses.](#)

CONSTRUCTION

Injection-molded, flame-retardant, high-impact, thermoplastic housing with snap-fit design components with LED lamps for easy installation. Universal J-box pattern (j-box not included). Track and swivel arrangement permits full range of lamp adjustment.

OPTICS

The typical life of the LED is 10 years. Two 1W LED lamps for emergency light.

Optional high-output battery to power both local and optional LED remote lamp heads simultaneously. The HO option provides additional 3W of LED remote capacity (up to 2 LED remote heads).

CCT: 5000K - 9000K

ELECTRICAL

Dual voltage input capability (120V/277V, 60hz) standard. Optional 120/347V, 60hz meets Canadian standards. Emergency unit provided with test switch, status indicator and rechargeable battery.

Battery: Maintenance-free nickel-cadmium battery provides 90 minutes of emergency power.

Self-diagnostics: Performs monthly 30 second, bi-monthly 30 minute and annual 90 minute testing with multi-status diagnostic functions.

INSTALLATION

Wall mount only (not suitable for ceiling mount).

LISTINGS

UL Listed. Meets UL 924, NFPA 101 (current Life Safety Code), NFPA 70-NEC, California Energy Commission Title 20 section 1605.3 (W)(4), FCC Title 47, Part 15, Subpart B and OSHA illumination standards. Indoor damp location 50°F to 104°F (10°C to 40°C) listed standard. CSA certified to Canadian C22.2 No. 141.15 standards.

WARRANTY

2-year limited warranty. Complete warranty terms located at:

www.acuitybrands.com/support/customer-support/terms-and-conditions

All life safety equipment, including emergency lighting for path of egress must be maintained, serviced, and tested in accordance with all National Fire Protection Association (NFPA) and local codes. Failure to perform the required maintenance, service, or testing could jeopardize the safety of occupants and will void all warranties.

NOTE: Actual performance may differ as a result of end-user environment and application.

All values are design or typical values, measured under laboratory conditions at 25 °C.



Specifications subject to change without notice.

† Small Battery Chargers Certified in the CA Title 20 Appliance Efficiency Database.

Lithonia Lighting Basics™ LED Emergency Light

EU2C

LED Lamps



Weight (shipping): 1.7 lbs. (0.77 kgs.)

All dimensions are inches (centimeters) unless otherwise indicated.

EU2C Emergency Light

CS Looking for Contractor Select readily available configurations? Click here to visit Contractor Select™ spec sheet or go to www.contractorselect.com

ORDERING INFORMATION For shortest lead times, configure product using **bolded options**. **Example: EU2C**

| Series | Housing Color | Voltage | Options |
|-----------------------------|---------------------------------------|---|--|
| EU2C Emergency Light | (Blank) Ivory white B Black | (Blank) 120/277VAC 120/347 120/347VAC | (Blank) Not Required HO High Output ¹ SD Self Diagnostics ² |

- Notes:**
- HO not available with SD option.
 - SD not available with HO (High Output).

Accessories: Order as separate items.

| | |
|----------------------|--|
| ELA WG1 | Wireguard (back mount only) ¹ |
| ERE W SGL SQ M12 | Single, LED indoor remote head, square, ivory white, 1W, 3.6V-12V voltage sensing ^{2,3} |
| ERE WT SQ M12 | Twin, LED indoor remote head, square, ivory white, 2W, 3.6V-12V voltage sensing ^{2,3} |
| ERE GY SGL WP SQ M12 | Single, LED weather-proof remote head, square, gray 1W, 3.6V-12V voltage sensing ^{2,3} |
| ERE GY T WP SQ M12 | Twin, LED weather-proof remote head, square, gray 2W, 3.6V-12V voltage sensing ^{2,3} |
| ERE GY SGL WP RD M12 | Single, LED weather-proof head, round, gray, 0.75W, 3.6V input ^{2,3} |
| ERE GY T WP RD M12 | Twin, LED weather-proof head, round, gray, 1.5W, 3.6V input ^{2,3} |

- Accessories Notes:**
- See spec sheet [ELA-WG](#).
 - Available with HO option only.
 - See spec sheet [ERE](#) remote head for additional ordering options

| Description | Supply Voltage | Input Wattage | | Input Amps | |
|-----------------------------|----------------|---------------|-----|------------|------|
| | | 120 | 277 | 120 | 277 |
| Standard (No Options) | 120/277 | .56 | .70 | .072 | .072 |
| High Output Option (HO) | 120/277 | .81 | 1 | .12 | .12 |
| Self Diagnostic Option (SD) | 120/277 | .06 | .75 | .09 | .09 |

| Description | Supply Voltage | Input Wattage | | Input Amps | |
|-----------------------------|----------------|---------------|------|------------|-------|
| | | 120V | 347V | 120V | 347V |
| Standard (No Options) | 120/347 | 2 | 2 | 0.023 | 0.008 |
| High Output Option (HO) | 120/347 | 3 | 3 | 0.025 | 0.009 |
| Self Diagnostic Option (SD) | 120/347 | 2 | 2 | 0.023 | 0.008 |

| Battery | Remote Capacity* | Maximum# Remote Lamp Heads* |
|---------|------------------|-----------------------------|
| 3.6V | 3W | 2 - ERE W SGL SQ M24 |
| | | 1 - ERE WT SQ M24 |
| | | 2 - ERE GY SGL WP SQ M12 |
| | | 1 - ERE GY T WP SQ M12 |
| | | 3 - ERE W SGL WP RD M12 |
| | | 2 - ERE W T WP RD M12 |

*These are in addition to the lamp heads on the product

SPACING GUIDELINES

*Note: To see complete photometric report or download the .ies file for this product, visit Lithonia Lighting EU2C home page.

| Maximum Spacing Guidelines — EU2C ¹ | | | | | | |
|--|--------------------|-------------------|-------------------|---------------------|-------------------|---|
| Mounting Height | Illumination Level | Single Luminaire | | Multiple Luminaires | | Application Notes |
| | | 3' Path of Egress | 6' Path of Egress | 3' Path of Egress | 6' Path of Egress | |
| 7.5' | 1FC Avg | 10' | 6' | 14' | 11' | 100' Corridor 8' wide, and 9' high with 80/50/20 reflectances |

- Notes:**
- Also meets the additional illumination requirements of NFPA 101: 1FC minimum and max/min ratio of 40:1.

