



ADDITIONAL KEY FEATURES

- 3G vibration rated per ANSI C136.31
- IP66 Rated

HYLINE501 RGBW

Housing	Extruded aluminum one-piece construction with fasteners
Available Section lengths	2ft, 3ft, or 4ft
CCT	Dynamic RGBW/RDM
Lumens	800 max lumens per foot
Optics	9° x 9°, 10° x 60°, 15° x 30°, 30° x 60°, 40° x 60°, 60° x 60°, Asymmetric Wall Wash
Voltage	120V - 277V
Controls	DMX



ADDITIONAL KEY FEATURES

- 3G vibration rated per ANSI C136.31
- IP66 Rated

HYLINE501 STATIC WHITE

Housing	Extruded aluminum one-piece construction with fasteners
Available Section lengths	2ft, 3ft, or 4ft
CCT	27K, 30K, 35K 40K, 50K
Lumens	1000 max lumens per foot
Optics	9° x 9°, 10° x 60°, 15° x 30°, 30° x 60°, 40° x 60°, 60° x 60°, Asymmetric Wall Wash
Voltage	120V - 277V
Controls	0-10V, Dali, DMX



ADDITIONAL KEY FEATURES

- 3G vibration rated per ANSI C136.31
- IP66 Rated

HYLINE501 MONOCHROMATIC COLOR

Housing	Extruded aluminum one-piece construction with fasteners
Available Section lengths	2ft, 3ft, or 4ft
CCT	Red, Green, Blue and Amber
Lumens	1000 max lumens per foot
Optics	9° x 9°, 10° x 60°, 15° x 30°, 30° x 60°, 40° x 60°, 60° x 60°, Asymmetric Wall Wash
Voltage	120V - 277V
Controls	0-10V, Dali, DMX



ADDITIONAL KEY FEATURES

- 3G vibration rated per ANSI C136.31
- IP66 Rated

HYLINE501 WDIM

Housing	Extruded aluminum one-piece construction with fasteners
Available Section lengths	2ft, 3ft, or 4ft
CCT	Golden range (30K-22K)
Lumens	1000 max lumens per foot
Optics	9° x 9°, 10° x 60°, 15° x 30°, 30° x 60°, 40° x 60°, 60° x 60°, Asymmetric Wall Wash
Voltage	120V - 277V
Controls	0-10V, Dali, DMX



ADDITIONAL KEY FEATURES

- 3G vibration rated per ANSI C136.31
- IP66 Rated

HYLINE501 TUWH

Housing	Extruded aluminum one-piece construction with fasteners
Available Section lengths	2ft, 3ft, or 4ft
CCT	Warm Neutral, Cool 3-Channel tunable white. Rhythm Range (65K-27K) or Layer Range (50K-22K)
Lumens	1000 max lumens per foot
Optics	9° x 9°, 10° x 60°, 15° x 30°, 30° x 60°, 40° x 60°, 60° x 60°, Asymmetric Wall Wash
Voltage	120V - 277V
Controls	DMX



ADDITIONAL KEY FEATURES

- 3G vibration rated per ANSI C136.31
- IP66 Rated

HYCOVE502 RGBW

Housing	Extruded aluminum one-piece construction with fasteners
Available Section lengths	2ft, 3ft, or 4ft
CCT	RGBW
Lumens	750 max lumens per foot
Optics	120° x 120°
Voltage	120V - 277V
Controls	DMX



ADDITIONAL KEY FEATURES

- 3G vibration rated per ANSI C136.31
- IP66 Rated

HYCOVE502 STATIC WHITE

Housing	Extruded aluminum one-piece construction with fasteners
Available Section lengths	2ft, 3ft, or 4ft
CCT	27K, 30K, 35K, 40K, 50K
Lumens	1000 max lumens per foot
Optics	120° x 120°
Voltage	120V - 277V
Controls	0-10V, Dali, DMX



ADDITIONAL KEY FEATURES

- 3G vibration rated per ANSI C136.31
- IP66 Rated

HYCOVE502 MONOCHROMATIC COLOR

Housing	Extruded aluminum one-piece construction with fasteners
Available Section lengths	2ft, 3ft, or 4ft
CCT	Red, Green, Blue and Amber
Lumens	1000 max lumens per foot
Optics	120° x 120°
Voltage	120V - 277V
Controls	0-10V, Dali, DMX



ADDITIONAL KEY FEATURES

- 3G vibration rated per ANSI C136.31
- IP66 Rated

HYCOVE502 WDIM

Housing	Extruded aluminum one-piece construction with fasteners
Available Section lengths	2ft, 3ft, or 4ft
CCT	Golden range (30K-22K)
Lumens	1000 max lumens per foot
Optics	120° x 120°
Voltage	120V - 277V
Controls	0-10V



HYCOVE502 TUWH

ADDITIONAL KEY FEATURES

- 3G vibration rated per ANSI C136.31
- IP66 Rated

Housing	Extruded aluminum one-piece construction with fasteners
Maximum Section lengths	Available in 2ft, 3ft, or 4ft
CCT	Warm Neutral, Cool 3-Channel tunable white Rhythm Range (65K-27K) or Layer Range (50K-22K)
Lumens	1000 max lumens per foot
Optics	120° x 120°
Voltage	120V - 277V
Controls	DMX



4750L STATIC WHITE LINEAR FLOOD

ADDITIONAL KEY FEATURES

- IP67 Rated
- Modular Flow-Thru and Taper-Lock Technology
- 3G vibration rated per ANSI C136.31

Housing	Copper free die cast aluminum and corrosion resistant extruded aluminum. All stainless steel fasteners
Available Section lengths	2ft or 4ft
CCT	27K, 30K, 35K, 40K, 50K, Amber
Lumens	2000 max lumens per foot
Optics	15°x15°, 25°x15°, 60°x15°, 95°x15°, Wall wash Asymmetric
Voltage	120V - 277V, 347V
Controls	0-10V, Dali, DMX



4750L LINEAR FLOOD RGBW

ADDITIONAL KEY FEATURES

- IP67 Rated
- Modular Flow-Thru and Taper-Lock Technology
- 3G vibration rated per ANSI C136.31

Housing	Copper free die cast aluminum and corrosion resistant extruded aluminum. All stainless steel fasteners
Available Section lengths	4ft
CCT	Dynamic RGBW/RDM
Lumens	1000 max lumens per foot
Optics	15°x15°, 25°x15°, 60°x15°, 95°x15°, Wall wash Asymmetric
Voltage	120V - 277V
Controls	DMX



ADDITIONAL KEY FEATURES

- IP67 Rated
- Modular Flow-Thru and Taper-Lock Technology
- 3G vibration rated per ANSI C136.31

4750L LINEAR FLOOD TUWH

Housing	Copper free die cast aluminum and corrosion resistant extruded aluminum. All stainless steel fasteners
Max Fixture Length	4ft
CCT	Warm Neutral, Cool 3-Channel tunable white. Rhythm Range (65K-27K)
Lumens	1000 max lumens per foot
Optics	15°x15°, 25°x15°, 60°x15°, 95°x15°, Wall wash Asymmetric
Voltage	120V - 277V
Controls	DMX



ADDITIONAL KEY FEATURES

- IP67 Rated
- Modular Flow-Thru and Taper-Lock Technology
- 3G vibration rated per ANSI C136.31

4750L INJB STATIC WHITE

Housing	Copper free die cast aluminum and corrosion resistant extruded aluminum. All stainless steel fasteners
Available Section lengths	4ft
CCT	27K, 30K, 35K, 40K, 50K
Lumens	2000 max lumens per foot
Optics	15°x15°, 25°x15°, 60°x15°, 95°x15°, Wall wash Asymmetric
Voltage	347V
Controls	0 - 10V, Reverse Phase



ADDITIONAL KEY FEATURES

- IP67 Rated
- Modular Flow-Thru and Taper-Lock Technology
- 3G vibration rated per ANSI C136.31

4750LCR CONTINUOUS LINEAR FLOOD

Housing	Low copper content housing materials, stainless steel fasteners, and durable powder coat finish options
Available Section lengths	2ft and 4ft
CCT	27K, 30K, 35K, 40K, 50K, Amber
Lumens	2000 max lumens per foot
Optics	VNSP (10x), NSP (20x), MFL (55x), WFL (100x), WWD (wall wash Asymmetric)
Voltage	120V - 277V, 347V
Controls	0-10V, Dali, DMX



ADDITIONAL KEY FEATURES

- IP67 Rated
- Modular Flow-Thru and Taper-Lock Technology
- 3G vibration rated per ANSI C136.31

4750LCR CONTINUOUS LINEAR FLOOD TUWH

Housing	Copper free die cast aluminum and corrosion resistant extruded aluminum. All stainless-steel fasteners
Available Section lengths	4ft Increments
CCT	Warm Neutral, Cool (3 channel tunable white)
Lumens	1000LMF
Optics	15x120°, 25x120°, 60x120°, 95x120°, Wall Wash
Voltage	120-277 volt
Controls	DMS Dark



ADDITIONAL KEY FEATURES

- IP67 Rated
- Modular Flow-Thru and Taper-Lock Technology
- 3G vibration rated per ANSI C136.31

4750LCR CONTINUOUS LINEAR FLOOD RGBW

Housing	Copper free die cast aluminum and corrosion resistant extruded aluminum. All stainless-steel fasteners
Available Section lengths	4ft Increments
CCT	Dynamic RGBW/RDM
Lumens	1000LMF
Optics	15x120°, 25x120°, 60x120°, 95x120°, Wall Wash
Voltage	120-277 volt
Controls	DMS Dark

Please refer to specific spec sheets for full list of options.