



M9400C

In-Grade Luminaire

HIGHLIGHTS

- Factory-sealed LED lamp module and encapsulated power module
- Optical and mechanical aiming with an optional double lens
- Optimal efficiency through photometric improvements
- Color temperature: 27K - 50K
- In-line & 0-10V Dimming
- Seven distributions including very narrow spot & wall wash
- Flow-through technology
- IK09 (IK10 option available)

5
YEAR
warranty



IP68



Specifications	SINGLE LENS	DOUBLE LENS
Length:	9"	9"
	229 mm	229 mm
Width:	9"	9"
	229 mm	229 mm
Height:	16"	16"
	407 mm	407 mm
Weight:	21lbs	23lbs

Weight is based on aluminum material.
For B and SS material add 2lbs.

DIMENSIONS




LUMEN PACKAGES


	VNSP	NSP	NFL	MFL	FL	WFL	WWD
Delivered Lumens	2,425	2,527	2,426	2,154	2,254	1,955	1,550
Watts	20	20	20	20	20	20	20
LPW	119	128	123	109	114	99	78
Peak Candela	22,634	15,940	14,728	3,364	2,097	1,423	1,729

Note: Information based on 4000K @ P2 Performance Package -
Single lens (M9410C and M9430C)


STANDARD DISTRIBUTION



AIMING DETAILS



Single lensed fixture can be aimed using
10° and 20° optical tilt lenses only.



Double lens, mechanically and optically aimed.

ORDERING INFORMATION

EXAMPLE: M9420C SS LED P3 40K MVOLT NSP FLC 34S

Model*	Door Material*	Source*	Performance Package*	LED Color*	Voltage*	Distribution*	Lens**
M9410C	Round Door, Single Lens	A Aluminum	LED P1 10W	27K 2700K	MVOLT (120 - 277 volt 50/60HZ)	NSP Narrow Spot	FLC Flat Lens Clear
M9420C	Round Door, Double Lens	B Bronze SS Stainless Steel	P2 20W P3 28W P4 ¹ 31W	30K 3000K 35K 3500K 40K 4000K		NFL Narrow Flood MFL Medium Flood	FLC5 Flat Lens Clear, 5° Axial Spread FLC10 Flat Lens Clear, 10° optical tilt FLC20 Flat Lens Clear, 20° optical tilt
M9430C	Square Door, Single Lens	Note: Aluminum material is not available with M9430C and M9440C square door	P5 ²	50K 5000K		FL Flood	FLF Flat Lens Frosted
M9440C	Square Door, Double Lens			AMBLW ³ Amber Limited Wavelength		WFL Wide Flood WWD ⁴ Wall Wash VNSP Very Narrow Spot	FLCAS Flat Lens Clear, Anti-Slip FLC5AS Flat Lens Clear, 5° Axial Spread, Anti-Slip
Note: For 50K consult factory for lead times							

Lens (cont.)	Conduit Entries*	Accessories	Options	Finish ¹²	Listing
FLCSR ⁶ Flat Lens Clear Slip Resistant	12B 1/2" NPT Bottom 12S 1/2" NPT Side	Internal ^{8,9} IHL Internal Honeycomb Louver LSF Linear Spread Filter	LDIM 0-10V Dimming (Dims to Dark) IDIM ¹¹ Inline Dimming (Dims to Dark)	BL Black BZ Bronze DDB Dark Bronze DNA Natural Alum. GN Green GR Gray SND Sand STG Steel Gray TVG Terra Verde Green WH White _Z ¹³ Zinc Undercoat (i.e. BLZ)	IEC ^{7,14} Built to International Electro-technical Commission Standards. (50HZ applications only)
FLC5SR ⁶ Flat Lens Clear, 5° Axial Spread, Slip Resistant	34B 3/4" NPT Bottom 34S 3/4" NPT Side	External ^{8,10} GS Glare Shield LC ¹⁰ Lexan Cover RG Rock Guard Note: For IK10 use external RG option			
FLC10SR ⁶ Flat Lens Clear, 10° optical tilt, Slip Resistant	25S ⁷ 25mm Side	Trim Ring ^{8,10} BTR Brass Round BTS Brass Square STR Stainless Round STS Stainless Square			
FLC20SR ⁶ Flat Lens Clear, 20° optical tilt, Slip Resistant	Note: Two (2) bottom or side entries available				

Note: * is a required field

ELECTRICAL LOAD

Light Engines	Drive Current (mA)	System Watts	Current (A)			
			120	208	240	277
P1	250mA	10	0.083	0.048	0.042	0.036
P2	500mA	20	0.167	0.096	0.083	0.072
P3	700mA	28	0.233	0.135	0.117	0.101
P4	850mA	31	0.258	0.149	0.129	0.112
P5	1050mA	14	0.117	0.067	0.058	0.051

PROJECTED LED LUMEN MAINTENANCE

Data references the extrapolated performance projections for the Fixture platform in a 25°C ambient, based on 13,000 hours of LED testing (tested per IESNA LM-80-08 and projected per IESNA TM-21-11).

To calculate LLF, use the lumen maintenance factor that corresponds to the desired number of operating hours below. For other lumen maintenance values, contact factory.

Based on 2700K-5000K LED color

Operating Hours	0	25,000	50,000	100,000
Lumen Maintenance Factor	1.00	0.91	0.85	0.75
Lumen Maintenance Factor*	1.00	0.94	0.94	0.93

*For VNSP only

- Notes:
- P3 with VNSP and P4 not available with double lens.
 - P5 only available with AMBLW.
 - AMBLW not available with VNSP or NSP distribution.
 - Recommended to use the FLF or FLCSR lens with the WWD. WWD distribution is not available with double lens.
 - Specify top lens. Bottom lens is FLC standard on M9420C and M9440C.
 - Meets ADA requirements for coefficient of friction.
 - Only for use in 50HZ applications.
 - Accessories are mutually exclusive, choose one only.
 - Not available with FLC10, FLC20, FLC10SR or FLC20SR.
 - External accessory not available with SS door material.
 - IDIM option should be run at 120 volt.
 - Finish only available on "A" door material.
 - Add Zinc undercoat for harsh environments.
 - Product is built to IEC standards but not listed.

LUMEN AMBIENT TEMPERATURE (LAT) MULTIPLIERS

Use these factors to determine relative lumen output for average ambient temperatures from 0-40°C (32-104°F).

Based on 2700K-5000K LED color

Ambient	Lumen Multiplier	Lumen Multiplier*	
0°C	32°F	1.05	1.06
10°C	50°F	1.03	1.04
20°C	68°F	1.01	1.01
25°C	77°F	1	1
30°C	86°F	0.99	0.99
40°C	104°F	0.96	0.96


*For VNSP only

SLIP RESISTANCE AND LOAD RATING


M9400C LED
MAXIMUM LOAD RATING Peak compression force of 7,700 lbs. (single lens), 2,550 lbs. (double lens).
LENS STATIC COEFFICIENT OF FRICTION M9400C Anti-Slip Lens (FLCAS): Dry = 0.76; Wet = 0.10 M9400C Slip Resistant Lens (FLCSR): Dry = 0.66; Wet = 0.67

M9400C LED Series Assembly consists of the following individual components parts	MRISC94 Rough-In Housing MFSC94 Finishing Section MACSC LED Module MHSLC94Power Module
---	---


PERFORMANCE DATA




NSP 2x2




NFL 3x3




MFL 4x4




FL 5x5



WFL 6x6



WWD 6X5



VNSP 1X1

To see complete photometric reports or download .ies files for this product, visit www.hydrrel.com

PERFORMANCE DATA

LUMEN OUTPUT – SINGLE LENS (M9410C AND M9430C)

Lumen values are from photometric tests performed in accordance with IESNA LM-79-08. Data is considered to be representative of the configurations shown, within the tolerances allowed by Lighting Facts. Actual performance may differ as a result of end-user environment and application. Contact factory for performance data on any configurations not shown here.

Performance Package	System Watts	Distribution Type	Field Angle		Beam Angle		27K (2700K, 80CRI)			30K (3000K, 80CRI)			35K (3500K, 80CRI)			40K (4000K, 80CRI)			50K (5000K, 80CRI)			AMBLW							
			°H	°V	°H	°V	Max Cd	Lumens	LPW	Max Cd	Lumens	LPW	Max Cd	Lumens	LPW	Max Cd	Lumens	LPW	Max Cd	Lumens	LPW	Max Cd	Lumens	LPW	Max Cd	Lumens	LPW		
P1	10 watts	VNSP	27	28	12	12	11,378	1,219	121	11,774	1,262	125	12,125	1,299	129	12,389	1,328	131	12,433	1,332	132								
		NSP	40	38	15	15	7,685	1,218	123	7,959	1,262	128	8,199	1,300	132	8,358	1,325	134	8,391	1,330	135								
		NFL	34	35	15	15	7,101	1,169	118	7,354	1,211	123	7,576	1,248	126	7,722	1,272	129	7,753	1,277	129								
		MFL	61	58	50	44	1,622	1,038	105	1,680	1,075	109	1,730	1,108	112	1,764	1,129	114	1,771	1,134	115								
		FL	77	84	61	72	1,011	1,087	110	1,047	1,125	114	1,079	1,159	117	1,100	1,182	120	1,104	1,187	120								
		WFL	93	85	77	68	686	942	95	711	976	99	732	1,005	102	746	1,025	104	749	1,029	104								
		WWD	84	76	70	46	834	747	76	863	774	78	889	797	81	907	813	82	910	816	83								
P2	20 watts	VNSP	27	28	12	12	20,788	2,228	109	21,511	2,305	113	22,153	2,374	116	22,634	2,425	119	22,715	2,434	119								
		NSP	40	38	15	15	14,657	2,324	117	15,179	2,406	122	15,637	2,479	125	15,940	2,527	128	16,003	2,537	128								
		NFL	34	35	15	15	13,542	2,230	113	14,025	2,310	117	14,448	2,379	120	14,728	2,426	123	14,787	2,435	123								
		MFL	61	58	50	44	3,093	1,981	100	3,203	2,051	104	3,300	2,113	107	3,364	2,154	109	3,377	2,162	109								
		FL	77	84	61	72	1,928	2,073	105	1,997	2,146	109	2,057	2,211	112	2,097	2,254	114	2,106	2,263	114								
		WFL	93	85	77	68	1,309	1,797	91	1,355	1,861	94	1,396	1,917	97	1,423	1,955	99	1,429	1,962	99								
		WWD	84	76	70	46	1,590	1,425	72	1,647	1,476	75	1,696	1,520	77	1,729	1,550	78	1,736	1,556	79								
P3	30 watts	VNSP	27	28	12	12	26,186	2,806	95	27,096	2,904	98	27,905	2,990	101	28,512	3,055	103	28,613	3,066	103								
	27 watts	NSP	40	38	15	15	19,329	3,064	112	20,017	3,173	116	20,622	3,269	119	21,021	3,333	122	21,105	3,346	122								
		NFL	34	35	15	15	17,859	2,941	107	18,495	3,046	111	19,054	3,138	114	19,423	3,199	117	19,500	3,211	117								
		MFL	61	58	50	44	4,079	2,612	95	4,224	2,705	99	4,352	2,787	102	4,436	2,841	104	4,454	2,852	104								
		FL	77	84	61	72	2,543	2,733	100	2,634	2,831	103	2,713	2,916	106	2,766	2,972	108	2,777	2,984	109								
		WFL	93	85	77	68	1,726	2,370	86	1,788	2,455	90	1,842	2,529	92	1,877	2,578	94	1,885	2,588	94								
		WWD	84	76	70	46	2,097	1,879	69	2,171	1,946	71	2,237	2,005	73	2,280	2,044	75	2,289	2,052	75								
P4	33 watts	NSP	40	38	15	15	22,891	3,629	109	23,707	3,758	113	24,423	3,872	117	24,895	3,947	119	24,994	3,963	119								
		NFL	34	35	15	15	21,151	3,483	105	21,904	3,607	109	22,566	3,716	112	23,002	3,788	114	23,094	3,803	114								
		MFL	61	58	50	44	4,831	3,093	93	5,003	3,203	96	5,154	3,300	99	5,254	3,364	101	5,275	3,377	102								
		FL	77	84	61	72	3,012	3,237	97	3,119	3,352	101	3,213	3,454	104	3,275	3,520	106	3,289	3,534	106								
		WFL	93	85	77	68	2,044	2,807	85	2,117	2,907	88	2,181	2,995	90	2,223	3,053	92	2,232	3,065	92								
		WWD	84	76	70	46	2,483	2,226	67	2,572	2,305	69	2,649	2,375	71	2,701	2,421	73	2,711	2,430	73								
P5	14 watts	NFL	5	30	3	3																4,375	355	25					
		MFL	74	79	61	63																	393	303	21				
		FL	96	96	82	81																		218	283	20			
		WFL	98	95	79	78																			187	245	17		
		WWD	82	83	55	40																				220	197	14	

OPERATING TEMPERATURE: -20°C through 50°C P1, P2 & P5; -20°C through 35°C P3; -20°C through 25°C P3 (VNSP), P4.

PERFORMANCE DATA

LUMEN OUTPUT – DOUBLE LENS (M94W0C AND M9440C)


Lumen values are from photometric tests performed in accordance with IESNA LM-79-08. Data is considered to be representative of the configurations shown, within the tolerances allowed by Lighting Facts. Actual performance may differ as a result of end-user environment and application. Contact factory for performance data on any configurations not shown here.

Performance Package	System Watts	Distribution Type	Field Angle		Beam Angle		27K (2700K, 80CRI)			30K (3000K, 80CRI)			35K (3500K, 80CRI)			40K (4000K, 80CRI)			50K (5000K, 80CRI)			AMBLW		
			°H	°V	°H	°V	Max Cd	Lumens	LPW	Max Cd	Lumens	LPW	Max Cd	Lumens	LPW	Max Cd	Lumens	LPW	Max Cd	Lumens	LPW	Max Cd	Lumens	LPW
P1	10 watts	VNSP	31	31	14	14	9,137	950	94	9,455	983	97	9,737	1,012	100	9,949	1,034	102	9,984	1,038	103			
		NSP	40	39	16	16	6,888	933	94	7,133	966	98	7,349	996	101	7,491	1,015	103	7,521	1,019	103			
		NFL	38	37	16	15	5,558	788	80	5,755	816	83	5,929	840	85	6,044	856	87	6,068	860	87			
		MFL	61	59	49	47	1,358	904	91	1,407	936	95	1,449	965	98	1,477	983	99	1,483	987	100			
		FL	57	72	37	53	920	712	72	953	737	75	982	760	77	1,001	774	78	1,005	777	79			
		WFL	66	66	52	53	726	506	51	752	524	53	775	539	55	790	550	56	793	552	56			
P2	20 watts	VNSP	31	31	14	14	16,694	1,735	85	17,274	1,795	88	17,790	1,849	91	18,176	1,889	92	18,241	1,896	93			
		NSP	40	39	16	16	13,136	1,780	91	13,604	1,843	94	14,015	1,899	97	14,286	1,936	99	14,343	1,943	99			
		NFL	38	37	16	15	10,599	1,502	76	10,977	1,555	79	11,308	1,602	82	11,527	1,633	83	11,573	1,640	83			
		MFL	61	59	49	47	2,590	1,724	88	2,683	1,786	91	2,764	1,840	94	2,817	1,875	95	2,829	1,883	96			
		FL	57	72	37	53	1,755	1,358	69	1,818	1,406	72	1,872	1,449	74	1,909	1,477	75	1,916	1,482	75			
		WFL	66	66	52	53	1,385	964	49	1,435	998	51	1,478	1,029	52	1,506	1,049	53	1,512	1,053	54			
P3	27 watts	NSP	40	39	16	16	17,323	2,347	83	17,941	2,431	86	18,483	2,504	88	18,840	2,553	90	18,915	2,563	90			
		NFL	38	37	16	15	13,978	1,981	70	14,476	2,051	72	14,913	2,113	74	15,202	2,154	76	15,262	2,163	76			
		MFL	61	59	49	47	3,416	2,274	80	3,538	2,355	83	3,645	2,426	85	3,715	2,473	87	3,730	2,483	87			
		FL	57	72	37	53	2,314	1,791	63	2,397	1,854	65	2,469	1,910	67	2,517	1,947	69	2,527	1,955	69			
		WFL	66	66	52	53	1,827	1,271	45	1,892	1,317	46	1,949	1,357	48	1,987	1,383	49	1,995	1,388	49			
P5	14 watts	NFL	5	30	3	3																3,535	227	16
		MFL	72	73	53	54																359	249	18
		FL	69	68	55	56																228	154	11
		WFL	64	68	46	55																173	113	8


OPERATING TEMPERATURE: -20°C through 50°C P1, P2 & P5; -20°C through 40°C P3.

ACCESSORIES

INTERNAL




INTERNAL HONEYCOMB LOUVERS — IHL
Hexagonal cell louver with 45° cut-off.




LINEAR SPREAD FILTER — LSF
6.68" diameter, spreads the beam of light along one axis only. May be oriented to spread the light horizontally or vertically.


EXTERNAL



QUARTER GLARE SHIELDS — GS
Rolled sheet aluminum or brass. 360° of adjustment on fixture door, with lock down. May be field installed to door as shown.
(Not recommended for foot traffic areas.)



ROCKGUARD — RG
Cast aluminum or cast bronze material.
(Not recommended for foot traffic areas.)



STAINLESS STEEL or BRONZE TRIM RINGS — BTR, BTS, STR, STS
A decorative escutcheon used when a high finish look is wanted. For finishing marble, tile or other installations. Available in round or square. Door is flush with escutcheon. Not available on SS doors.



LEXAN DOME — LC
A Lexan protective cover for use in areas where loose debris such as leaves and pine needles accumulate.

SPECIFICATIONS AND FEATURES

INTENDED USE: The M9400C LED incorporates a modular design with a water-tight module and junction box intended for applications with flow-through capability. The design of the housing starts at the rough-in sections with a molded junction box and holes at the bottom, allowing a pathway for the water to flow through the housing and drain out the bottom. This product is ideal for all outdoor upright applications, such as wall washing and feature accentuation.

DOOR MATERIAL: Cast aluminum, cast bronze or stainless steel. Available in round or square door trim. Finish is natural aluminum or bronze. Stainless steel door is brushed finish. Aluminum doors may be painted. See ordering guide.

ROUGH-IN SECTION: Injection molded polymer with integral junction box for thru-branch wiring. The housing is U.V. stabilized, impact and corrosion resistant for use in all types of environments. The rough-in houses the LED and power module components and top door finishing section. Potting compound (PC21) recommended for junction box splices. PC21 sold separately.

CONDUIT ENTRIES: Two (2) bottom or side entries available. Box suitable for through-branch wiring. Splicing volume is 25 in³ (410 ccm)

FINISHING SECTION: Double lens design includes door assembly with 360° Aim-Lock™ module support and tilt ring that allows 15° of aiming. Active optical lenses are also available. Module indexing provides easy maintenance without re-aiming. Door trim locks into position with two stainless steel captive, tamper-resistant fasteners.

LED MODULE: Over molded brass housing, factory-sealed and purged of all moisture for longer component life. The LED module is suspended below the top door lens in a surface adjustable, 15° tilt mechanism. Lens is sealed with silicone gasket and stainless steel clamp band assembly with single fastener. Electrical connection to LED module is done through a submersible quick disconnect plug connector with gold-plated contacts.

LIGHT ENGINE: Light engine consist of a chip-on-board (COB) LED directly coupled to the housing to maximize heat dissipation and promote long life (100,000 hrs, L75) and (100,000 hrs, L93 for VNSP). All within 3 MacAdam ellipses

POWER MODULE: LED driver is encapsulated in a custom heat-dissipating epoxy resin that eliminates all moisture intrusion. Module is provided with submersible rated cord leads for connection to integral junction box and LED module.

ELECTRICAL: MVOLT (120-277) 50/60 Hz LED power supply. Class 2 electronic driver has a power factor >90%, THD <20%, and has an expected life of 100,000 hours with <1% failure rate. 6 kv Surge protection meets a minimum Category C Low operation (per ANSI/IEEE C62.41.2).

LISTING: cCSAus, suitable for wet locations, laboratory tests conducted by CSA to UL Standard UL-1598 and UL-8750.

GOVERNMENT PROCUREMENT

BAA – Buy America(n) Act: Product qualifies as a domestic end product under the Buy American Act as implemented in the FAR and DFARS. Product also qualifies as manufactured in the United States under DOT Buy America regulations.

BABA – Build America Buy America: Product qualifies as produced in the United States under the definitions of the Build America, Buy America Act.

Please refer to www.acuitybrands.com/resources/buy-american for additional information

WARRANTY: 5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at: www.acuitybrands.com/support/warranty/terms-and-conditions
Consult factory for details.

NOTE: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.